



Idenden T100

SELF-ADHESIVE REINFORCED FOIL TAPE

TECHNICAL SHEET NO: TDS00652 14/04/2023

SMART ADVANTAGES

- Fire tested
- Reinforced with 12mm² glass scrim
- High-tack adhesive


DESCRIPTION

Bostik T100 Self-Adhesive Reinforced Foil Tape is part of the market leading range of products for the heating, ventilation and air conditioning sectors. Bostik T100 is manufactured to the highest specifications. Bostik T100 is a bright aluminium foil tape reinforced with 12mm² glass scrim and kraft paper. The tape is coated with a high tack rubber/resin adhesive system and protected by a removable release paper. The reinforced foil improves mechanical damage resistance and is ideal for matching the foil finish on insulation.

It is easy to apply, exhibiting instant adhesion and can be moulded to any profile. The final bond has high shear strength and the foil promotes the optimum balance of surface conformity and tensile strength. This makes it ideal for lap sealing foil faced insulation materials, metal and duct sealing and other general-purpose applications.



TECHNICAL CHARACTERISTICS

Finish	Bright aluminium foil tape reinforced with 12mm ² glass scrim and kraft paper
Adhesive	Rubber/resin
Release paper	High quality siliconised paper
Application temperature	Above +5°C
Service temperature	-10°C to +90°C (depending on operating conditions)
Peel adhesion to steel	Initial: 20 to 25N/25mm 24 hours: 25 to 30N/25mm (approx.)
Fire tests	Independently tested to BS 476: Part 7 – Class 1 When tested as supplied, and applied to calcium silicate board. Results will vary when applied to other substrates UL Classified General Use Tapes R38033  Surface burning characteristics of building materials, UL723 Applied to inorganic reinforced cement board+

	<p>Flame spread 5 Smoke developed 10 + - Tested in two 76mm (3 in.) wide longitudinal strips spaced 203mm (8 in.) OC. (Tape coverage: 30 percent of the exposed test sample area.)</p> <p>Bostik T100 Self-Adhesive Reinforced Foil Tape meets the requirements of NFPA 90A and 90B (2018 edition) for a flame spread index of less than 25 and a smoke developed index of less than 50, when tested to ANSI/UL 723, Standard for Test for Surface Burning Characteristics of Building Materials by Underwriter's Laboratories</p>
VOC testing	<p>Bostik T100 Self-Adhesive Reinforced Foil Tape showed low VOC contents in a test specified in LEED 2009 EQ c 4.1 (adhesives and sealants). The VOC content is below the limit value specified as 30 grams/litre (less water) for 'Metal to Metal Adhesives': VOC g/l: 16</p>

use where the joint is subject to mechanical stress. In this instance, insulation should be fixed using a suitable adhesive or hanger system.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik T100 Self-Adhesive Reinforced Foil Tape, available at www.bostik.com/uk.

PACKAGING

Product codes	30813003	45m x 75mm x 16
----------------------	----------	-----------------

APPLICATION

IMPORTANT: Before using Bostik T100 Self-Adhesive Reinforced Foil Tape, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Surfaces to be bonded must be clean, dry and free from dust, grease and loose materials. If necessary, wipe surfaces sparingly with a cloth dampened with a ketone-free cleaner such as EVO-STIK Cleaner 4 and allow to dry for at least an hour before tape application.
- The butt joints of insulation sections should be positioned together without gaps to ensure an adequate bond.
- Select a tape width suitable for the application. A width of 50mm is suitable for closely positioned, flat sections. Otherwise, select a tape the thickness of the insulation plus 50mm to allow for the exposed cut edge.

APPLICATION

- Remove the release paper from a section of the tape, taking care not to touch the adhesive surface. Align the tape centrally over the joint. Pull the tape taut and then press down well over the entire joint area. Rub the tape to remove any wrinkles or folds.

STORAGE

- Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +10°C to +30°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

Bostik T100 Self-Adhesive Reinforced Foil Tape is intended for joint sealing applications only, and is therefore not suitable for

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left hand corner on the front of this document.

Sales	Tel: 0844 371 1192	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.