



Cementone Resin for Blocks

WET LOOK FINISH POLYURETHANE SAND BINDER AND BLOCK SEALER

Date: 13 January 2016

Fact Sheet No.: TDS00055

YOUR SMART ADVANTAGES

- Eliminates grass and weed growth
- Prevents re-occurrence of efflorescence
- Jet wash with no loss of sand

USES

Bostik Resin for Blocks Wet Look (formerly known as Cementone Resin for Blocks Wet Look) is a polyurethane sand binder and sealer for use on concrete block paving. Bostik Resin for Blocks Wet Look impregnates the blocks and the jointing sand. When dry, the sand and blocks are permanently bonded together to ensure the sand is not washed out of the joints and the paving is sealed from weed growth, efflorescence and stains.

Bostik Resin for Blocks Wet Look is suitable for concrete block paving only on well drained drives, paths and patios.

PRODUCT CHARACTERISTICS

Colour	Transparent, light straw
Odour	Aromatic solvent
Form	Thin liquid
Specific Gravity	0.9 approx.
Composition	Moisture curing polyurethane solution
Product Codes	30812552 5 Litre x 1 30812553 25 Litre x 1

Storage/Shelf Life

Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 12 months from date of manufacture in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +30°C and out of direct sunlight. Protect from frost. When opened, use within 48 hours, even if carefully re-sealed.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +30°C
Water Resistance	Excellent
Petrol & Oil Resistance	Excellent
Coverage	Coat 1: 3m ² per litre Coat 2: 6m ² per litre
Drying Times	Foot traffic: 4 to 6 hours Vehicular traffic: 24 to 48 hours Note: Lower temperatures will extend drying times.
Solvent for Cleaning Up	Wet product may be removed from non-porous surfaces using a cloth dampened in white spirit. Wet product on porous surfaces cannot be removed. Dried product can only be partially removed by mechanical means.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Resin for Blocks Wet Look refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Wear protective gloves, clothing and goggles.
2. Bostik Resin for Blocks Wet Look must only be applied within the temperature range of +5°C to +30°C.

Existing Block Paving:

3. Paving must be clean and free of dust, weeds, algae, stains and efflorescence.
4. Jet washing is recommended.
5. This may remove some of the jointing sand which must be replaced on the day the sealer is applied.
6. Replace or clean any badly stained blocks and treat efflorescence with Bostik Brick & Patio Cleaner.
7. Allow 2 weeks after cleaning to ensure efflorescence does not re-appear.

New Block Paving:

8. Paving must be clean and free of dust, weeds, algae, stains and efflorescence.
9. For best results clean the blocks with Bostik Brick & Patio Cleaner to remove efflorescence; then wash down thoroughly with clean water.
10. Allow 8 weeks after cleaning to ensure efflorescence does not re-appear.

Final Preparation:

11. On the day of sealing, ensure the paving is thoroughly dry. Allow a minimum of 48 hours after jet washing or rain. Brush fresh kiln dried sand into the joints with a soft broom.
12. Before applying the sealer, ensure there is no sand on the face or on the bevelled edges of the blocks.
13. Protect adjacent surfaces, ponds and plants from splashing.

APPLICATION

14. Bostik Resin for Blocks Wet Look is not suitable for interior use or around swimming pools.
15. Always test on a small inconspicuous area first and allow to dry prior to the full application to safeguard against unwanted changes of appearance to the surfaces.
16. Bostik Resin for Blocks Wet Look uses a two coat system for maximum protection and enhanced appearance.

First Coat:

17. Coat the perimeter of the area to be sealed up to the first joint line with a 10 cm (4 inch) paint brush.
18. Coat the blocks using a short pile roller. Work diagonally across the joints from side to side.
19. Apply at a rate of 3m² per litre to ensure good penetration.

20. Do not press too heavily on the roller.
21. Do not allow the sealer to pool.
22. If it is necessary to take a break, always stop along a joint line to avoid stripping.

Second Coat: (should be completed on the same day)

23. Apply the second coat after 3 to 4 hours, preferably on the same day but no longer than 24 hours after the first coat.
24. Work at right angles to the first coat and apply an even coat at 6m² per litre. It is important not to apply more than the stated coverage rates and ensure any excess is removed, do not allow to pool.
25. Leave sealed area to dry. This will take approximately 4 to 6 hours for foot traffic and 24 to 48 hours for vehicles. However, if the temperature falls below 10°C (e.g. overnight) the drying time will be extended.
26. It is recommended that you ensure the surface has dried fully and is not tacky before allowing vehicular traffic.

CLEANING

27. Wet Bostik Resin for Blocks Wet Look may be removed from smooth non-porous surfaces with white spirit. Clean at least twice with fresh solvent and cloth.
28. Wet Bostik Resin for Blocks Wet Look cannot be removed from porous surfaces.
29. Dried Bostik Resin for Blocks Wet Look can only be removed partially by mechanical means. Complete removal may not be possible.

PRECAUTIONS IN USE

Bostik Resin for Blocks Wet Look is not suitable for interior use due to the lingering odour of solvent. Do not use around swimming pools. Always test on a small inconspicuous area first and allow to dry prior to the full application to safeguard against unwanted changes of appearance to the surfaces. Do not press too heavily on the roller. Do not allow the sealer to pool. If it is necessary to take a break, always stop along a joint line to avoid stripping.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Resin for Blocks Wet Look, available at www.bostik.co.uk.

BOSTIK HOTLIN

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealcrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.