



Penetration Primer

FOR ROOFS

Date: 18 November 2016

Fact Sheet No.: TDS00072

YOUR SMART ADVANTAGES

- Apply before a bituminous coating
- For all common roof surfaces
- Spray or brush on

USES

Bostik Penetration Primer for Roofs is a highly penetrative, thin bituminous solution, black in colour. It is used for priming bitumen roofing felt, concrete roofs and floors, cementitious screeds/renders, mastic asphalt, weathered corrugated iron and steel prior to the application of bituminous coatings.

PRODUCT CHARACTERISTICS

Colour	Black
Form	Thin liquid
Specific Gravity	0.9 approx.
Composition	Solvent-borne bituminous solution
Product Codes	30811883 1 Litre x 6 30811889 2.5 Litre x 6 30811886 5 Litre x 4 30811887 22.5 Litre 30811891 200 Litre
Storage/Shelf Life	Store and transport this container in a secure upright position. Ensure the lid is secure. Store for up to 24 months from date of manufacture in original, unopened packaging undercool dry conditions within a temperature range of +5°C to +35°C out of direct sunlight and away from sources of heat and ignition.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +35°C (surfaces must be completely free of ice and water)
Service Temperature	-10°C to +85°C (depending on operating conditions)
Coverage	4 – 6m ² per litre dependent on the porosity of the surface
Drying Times	3 to 6 hours (depending on drying conditions)
Solvent for Cleaning Up	White spirit

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Penetration Primer for Roofs refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Ensure the roof surface is structurally sound, clean, dry and free from surface contaminants such as grease and dirt.
2. Remove any organic growth i.e. moss or lichen with Bostik Fungicidal Wash.
3. Rusty surfaces must be prepared then treated with the appropriate primer, often a zinc phosphate.

APPLICATION

4. Using a brush, scrub the Bostik Penetration Primer for Roofs well into the surface. Ensure that only a thin coat is applied and that there is no pooling. Allow to dry thoroughly before over coating. Where possible we recommend using disposable brushes for the application of Bostik Penetration Primer for Roofs.
5. Alternatively spray thinly and evenly. Allow to dry thoroughly before over coating.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

6. With fibre cement or old roofing felts, apply generously to saturate the surface.
7. Priming should extend at least 75mm beyond the area to be waterproofed.

CLEANING

8. Clean tools and equipment immediately after use with white spirit.
9. Dried product is difficult to remove.
10. Where possible we recommend using disposable brushes for the application of Bostik Penetration Primer for Roofs.

PRECAUTIONS IN USE

Colour indicated on pack is a guide only. It is recommended that users apply a small amount of Bostik Penetration Primer for Roofs in an inconspicuous area and allow to dry to determine colour suitability before commencing work. Shade variations may occur between batches. When completing projects requiring multiple tins please ensure that they are from the same batch. Please be aware that coating clear glass or clear plastic roofs or roof-lights might constitute a hazard.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Penetration Primer for Roofs, available at www.bostik.co.uk.



BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.