



# Cementone Mortar & Brick Cleaner

**STRONG ACID BASED BRICK CLEANER  
CONCENTRATED FOR TRADE USE ONLY**

Date: 24 August 2020

Fact Sheet No.: TDS00119

## YOUR SMART ADVANTAGES

- Powerful cleaner for stubborn cement stains
- Removes mortar stains and limescale
- Apply by brush

## USES

Bostik Mortar & Brick Cleaner is a strong hydrochloric acid based cleaner for trade use only. It's formulated to remove stubborn stains, limescale and engrained dirt quickly and efficiently. For exterior use only.

Bostik Mortar & Brick Cleaner can be used to remove heavy cement and mortar stains from brickwork, concrete, walls, scaffolding and tools (please see 'Precautions in Use' section).

## PRODUCT CHARACTERISTICS

Colour	Pale yellow
Form	Liquid
Specific Gravity	1.07 approx.
Composition	Solution of 16% hydrochloric acid
Product Code	30812503 5 litres x 4
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 2 years from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

## TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +25°C
Coverage	Undiluted: 4m <sup>2</sup> per litre (depending on application technique)
Mix Ratios	See table below
Cleaning	Clean tools and equipment with water immediately after use

## DIRECTIONS FOR USE

**IMPORTANT:** Before using Bostik Mortar & Brick Cleaner, refer to the relevant Health & Safety Data Sheet, available at [www.bostik.com/uk](http://www.bostik.com/uk).

## MIXING

1. Mix Bostik Mortar & Brick Cleaner only in plastic containers.

APPLICATION	MIX RATIO
General cleaning:	1 part Cleaner to 4 parts water
Heavy and severe staining:	Undiluted

## PREPARATION

2. Use protective goggles, gloves and clothing to cover face, eyes and skin when using Bostik Mortar & Brick Cleaner.
3. To prevent damage to windows and glass, mask with polythene. N.B. fumes will tarnish metals.
4. Do not apply Bostik Mortar & Brick Cleaner to, or near painted enamel, stainless steel, decorative brass, aluminium, natural limestone, sandstone, marble, terrazzo or lime/silicate bricks as this cleaner may discolour metal or attack decorative surfaces.

5. Always test on a small, concealed area before proceeding to clean the whole area. The test area should be examined after 24 hours as the effect is not immediately noticeable.

#### APPLICATION

##### Brickwork, concrete & paving etc.:

6. Dilute as stated.
7. Thoroughly wet the area to be treated with water to reduce the absorption of the cleaner.
8. Apply Bostik Mortar & Brick Cleaner with a soft brush, carefully scrubbing it into the surface.
9. It is vital that the cleaner is thoroughly rinsed off with plenty of water before it has had time to dry to avoid a white discolouration developing on the paving. This is very difficult to remove once formed. Do not use a power washer.
10. Repeat procedure if necessary.
11. When used on pigmented concrete some colour loss may occur.

##### Metal tools

12. See precautions in use below.
13. Soak tools in undiluted Bostik Mortar & Brick Cleaner for up to 2 hours.
14. Rinse tools thoroughly with water and allow to dry.
15. Apply an appropriate metal protector to prevent corrosion.
16. Do not use on power tools.

#### CLEANING

17. Clean tools and equipment with water immediately after use.
18. Clean at least twice to remove any remaining product residue.

#### PRECAUTIONS IN USE

This cleaner is for external use only.

Transport in an upright position, secured from tipping over. Store securely in the boot, not in the passenger compartment. Always store near the ground on a firm flat surface, in a safe position.

This cleaner gives off acidic fumes which can discolour metal or decorative surfaces. Do not use on or near painted enamel, stainless steel, decorative brass, aluminium, natural limestone, sandstone, marble, terrazzo or lime/silicate bricks. Hydrochloric acid dissolves calcium carbonate based materials i.e. marble, terrazzo, lime/silicate bricks, limestone and cement based paving. Dilute as stated and test on a small, concealed area before proceeding to clean the whole area. The test area should be examined after 24 hours as the effect is not immediately noticeable. If there is any indication that the acid is attacking the surface, wash the surface immediately with plenty of water. Do not use a jet

or power washer to rinse off the cleaner. When used on pigmented surfaces colour loss may occur. When removing spots of lime, lime-scale or cement it is best to apply the product only where needed.

Do not mix or use with any other chemicals. Protect lawns and plants during application and when rinsing away cleaner. Do not contaminate ponds, waterways or ditches with product.

Take care when using on metal surfaces as the acid may damage them. To prevent damage to windows and glass, mask with polythene.

Animals and children must be kept away from the treatment area during application and until the area is completely dry and free of any residual product.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.com/uk](http://www.bostik.com/uk) for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Mortar & Brick Cleaner, available at [www.bostik.com/uk](http://www.bostik.com/uk).

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>