

Flashband Primer Emulsion

FOR ROOFS

Date: 06 January 2016

Fact Sheet No.: TDS00177

YOUR SMART ADVANTAGES

- Improves grab and adhesion
- For porous, dusty or damp surfaces
- Primer for flashing tape

USES

Bostik Flashband Primer Emulsion for Roofs is a specially designed, structured rubber bitumen emulsion for aiding adhesion of Bostik Flashband to rough or porous building surfaces. Bostik Flashband Primer Emulsion for Roofs may also be used for smooth porous surfaces to improve adhesion. Bostik Flashband Primer Emulsion for Roofs can be used on surfaces that are damp, but not wet. For smooth non-porous surfaces use Bostik Flashband Primer S.V. Bostik Flashband Primer Emulsion for Roofs is not designed as a general purpose primer for other bitumen products.

PRODUCT CHARACTERISTICS

Colour	Dark brown, dries shiny black
Form	Low to medium viscosity liquid
Specific Gravity	1.0 approx.
Composition	Slightly structured, rubber/bitumen emulsion
Product Code	30812256 1 Litre x 12
Storage/Shelf Life	Store and transport this container in a secure upright position. Ensure the lid is secure. Store for up to 24 months from date of manufacture in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight. Protect from frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +35°C
Service Temperature	-10°C to +90°C
Coverage	2m ² per litre approx., depending on the porosity of the surface and its evenness.
Drying Times	20 minutes in good drying conditions up to several hours in cold, damp conditions
Solvent for Cleaning Up	Warm soapy water

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Flashband Primer Emulsion for Roofs refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. All surfaces should be sound, clean, preferably dry and free from surface contaminants such as grease, oil, rust, and dirt.
2. Remove any organic growth i.e. moss or lichen with Bostik Fungicidal Wash.
3. Surfaces must not have ice or liquid water present, but may be damp. Temperatures should be above 5°C.
4. Areas of rust should be thoroughly wire brushed and treated with a proprietary rust remover.

APPLICATION

5. Porous surfaces should be dampened with water immediately before application.

6. Where possible we recommend using disposable brushes for the application of Bostik Flashband Primer Emulsion for Roofs. Apply Bostik Flashband Primer Emulsion for Roofs with a soft bristle brush slightly in advance of where Bostik Flashband is to be applied.
7. Surfaces such as mineralised felt or textured brick may require 2 coats of Bostik Flashband Primer Emulsion for Roofs.
8. Allow Bostik Flashband Primer Emulsion for Roofs to dry before applying Bostik Flashband. Protect from rain and frost during the drying time.
9. Bostik Flashband Primer Emulsion for Roofs dries by loss of water. In warm, dry conditions the primer can dry in as little as 20 minutes. In cold, damp conditions, below 80% humidity it may take 2 hours.
10. When freshly applied Bostik Flashband Primer Emulsion for Roofs appears to be dark brown and dries to a shiny black.

CLEANING

11. Clean tools and equipment immediately after use with warm soapy water.
12. Dried product can be removed using white spirit or a proprietary brush cleanser.
13. Use proprietary hand cleansers for splashes on skin. Do not use solvents.

PRECAUTIONS IN USE

Do not use Bostik Flashband Primer Emulsion for Roofs over tar-based products. Do not use if the surface temperature is likely to rise above 65°C.

For any application not covered please contact Technical Services on +44(0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Flashband Primer Emulsion for Roofs available at www.bostik.co.uk.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.