



Aluminium Solar Protector

SILVACOTE FOR ROOFS

Date: 18 November 2016

Fact Sheet No.: TDS00407

YOUR SMART ADVANTAGES

- Solar reflective coating
- Immediate water resistance
- Brush or roller on

USES

Bostik Aluminium Solar Protector for Roofs is a bituminous based aluminium protective coating with light and heat reflective properties for use over bituminous coatings, aged asphalt and primed steel. It is of brushing consistency and dries to a silvery finish.

PRODUCT CHARACTERISTICS

Colour	Black upon opening, silver surface once thoroughly stirred
Form	Liquid
Specific Gravity	1.0 approx.
Composition	Filled bitumen solution in white spirit
Product Codes	30812224 5kg x 4 30812226 22.5kg
Storage/Shelf Life	Store and transport this container in a secure upright position. Ensure the lid is secure. Store for up to 24 months from date of manufacture in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +35°C out of direct sunlight and away from sources of heat and ignition.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +35°C
Service Temperature	-30°C to +90°C (depending on operating conditions)
Coverage	4 - 6m ² per litre per coat dependent on the porosity of the surface
Drying Times	Approximately 1 hour (dependent on drying conditions)
Solvent for Cleaning Up	White spirit or Paraffin (kerosene)

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Aluminium Solar Protector for Roofs refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Ensure the roof surface is structurally sound, clean, dry and free from surface contaminants such as grease, rust and dirt.
2. Remove any organic growth i.e. moss or lichen with Bostik Fungicidal Wash.
3. Do not apply when rain, frost or overnight dew are expected before the coating is fully dry, as bronzing of the surface may result if these conditions are not observed.
4. Bostik Aluminium Solar Protector for Roofs can only be applied to surfaces which are completely dry and great care must be taken to ensure that when applied to bitumen felt, no moisture is contained within the felt.



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

5. If the surface is still dusty after cleaning, or covered with weathered bitumen, prime with Bostik Penetration Primer for Roofs and allow to dry.

APPLICATION

6. Take care when opening the lid.
7. Mix contents thoroughly to the bottom of the drum before use for 10 to 15 minutes to obtain a uniform colour.
8. Do not thin. Apply immediately and continue stirring periodically during use.
9. Where possible we recommend using disposable brushes for the application of Bostik Aluminium Solar Protector for Roofs. Apply two thin coats of Bostik Aluminium Solar Protector for Roofs by brush or mohair roller. When brushing, use soft bristle brushes applying the lightest pressure.
10. The second coat should be applied as soon as the first coat is dry.
11. When applying over recently applied bituminous coatings, allow the following minimum times to elapse after the final coat has dried before applying Bostik Aluminium Solar Protector for Roofs:

Hot applied coatings: 24 hours

Solvent based coatings: 3 days

Water based coatings: 14 days

12. Over bituminous surfaces apply the thinnest coat necessary to fully cover the black colour of the bitumen underneath. The second coat should also be thin and applied at right angles to the first. Avoid the formation of pools.
13. When applying to large areas on bright days it is advisable to wear polarized sunglasses to reduce glare.

CLEANING

14. Clean tools and equipment immediately after use with white spirit or paraffin (kerosene).
15. Excess product can also be removed with white spirit or paraffin (kerosene).
16. Where possible we recommend using disposable brushes for the application of Bostik Aluminium Solar Protector for Roofs.

PRECAUTIONS IN USE

Bostik Aluminium Solar Protector for Roofs can only be applied to surfaces which are completely dry and great care must be taken to ensure that when applied to bitumen felt, no moisture is contained within the felt. Do not apply when rain, frost or overnight dew are expected before the coating is fully dry, as bronzing of the surface may result if these conditions are not observed. Do not thin. This product must be thoroughly mixed. Avoid pooling. Do not transport in cars, store securely in the boot.

Colour indicated on pack is a guide only. It is recommended that users apply a small amount of Bostik Aluminium Solar Protector for Roofs in an inconspicuous area and allow to dry to determine colour suitability before commencing work. Shade variations may occur between batches. When completing projects requiring multiple tins please ensure that they are from the same batch.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Aluminium Solar Protector for Roofs, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk

Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & COSHH (MSDS) Data Sheets	Tel: 01785 272625	Fax: 01785 212962	stafford.gatehouse@bostik.com



FM 01696
BS EN ISO 9001:2008

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 www.bostik.co.uk
Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.