



Flexacryl Quick Drying

WATERPROOFER FOR FLAT ROOFS

TECHNICAL SHEET NO: TDS01640 20/10/2023

SMART ADVANTAGES

- Fast drying & low-odour
- Contains fibres for flexibility & to bridge cracks
- No primer required

DESCRIPTION

Bostik Flexacryl Quick Drying Waterproofer is a fast drying, low-odour roof coating that waterproofs most conventional roofing substrates.

The fibres in Bostik Flexacryl Quick Drying Waterproofer bridge small cracks and enable the coating to flex with changes in temperature.

It can be brushed straight from the can onto substrates such as old roofing felt, asphalt, bituminous roof coatings, concrete, lead work, brickwork, metal*, slate and rigid PVC. It is also suitable for application to gutters and flashings.



TECHNICAL CHARACTERISTICS

Colour	Grey
Form	Viscous paste, containing fibres
Specific gravity	1.28 approx.
Composition	Co-polymer emulsion
Application temperature	+10°C to +30°C (external work should not be completed in poor drying conditions, or when rain is imminent)
Service temperature	-10°C to +85°C (depending on ambient conditions)
Drying time	Surface dry and resistant to light showers in 80 to 85 minutes at +10°C. This will be significantly reduced in warmer conditions (depending on coating thickness, ambient temperature and humidity)

COVERAGE

- 1L to 2L (approx.) per m²
(depending on substrate, application technique and performance requirements. Wet surfaces may require a second coat)

APPLICATION

IMPORTANT: Before using Bostik Flexacryl Quick Drying Waterproofer, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Ensure the roof is structurally sound, clean and free from dust, dirt, oil, grease, loose paint, stone chippings, rust, standing water and other surface contaminants.
- Remove any organic growth i.e., moss or lichen with Bostik Fungicidal Wash.
- *New metal surfaces should be degreased with a suitable solvent. Metal surfaces with residual rust remaining after cleaning should be treated with a zinc phosphate or other suitable rust inhibitive primer.
- Bostik Flexacryl Quick Drying Waterproofer can be applied to dry or damp surfaces. Ensure excess and pooled water has been brushed away. Wet or damp surfaces will extend drying times and a second coat may be required.

APPLICATION

- Bostik Flexacryl Quick Drying Waterproofer should be applied in temperatures above +10°C. External work should not be completed in poor drying conditions, or when rain is imminent.
- Stir thoroughly before use.
- We recommend using disposable brushes for the application of Bostik Flexacryl Quick Drying Waterproofer.
- Apply by brush straight from the container in a single, uniform coat, at a rate of 1 to 2 litres per m².
- In dry conditions, only one coat is required. Wet surfaces may require a second coat.
- Ensure gaps or cracks are completely covered as Bostik Flexacryl Quick Drying Waterproofer contains fibres that will bridge and seal them permanently. Cracks over 10mm should be covered with a suitable flexible scrim bedded into the coating.

DRYING TIME

- To test for dryness, gently rub the coating with a clean damp rag. If no colour is removed, then the film has dried effectively and will exhibit good water resistance.
- When applied on dry surfaces, the coating is resistant to light showers after 80 to 85 minutes at +10°C. However, drying of the film depends on the thickness of the coating and weather conditions. Heavy application, damp weather and/or low temperatures will extend the drying time. These times are significantly reduced in warmer conditions.

CLEANING

- Clean tools and equipment with water immediately after use. Cured coating can be removed with white spirit.

STORAGE

- Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 2 years from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

Do not apply Bostik Flexacryl Quick Drying Waterproofer in areas that will be exposed to foot traffic, and do not place heavy objects on top of areas coated with it. For areas where there is regular foot traffic, it is recommended that the coating is overlaid with promenade tiles, or a similar protective material.

Do not use Bostik Flexacryl Quick Drying Waterproofer in aquatic environments, or internally as a tanking membrane.

Do not apply over roof lights, glass or windows. Coating clear glass, or clear plastic roofs, or roof-lights might constitute a hazard.

Colour indicated on pack is a guide only. It is recommended that users apply a small amount of Bostik Flexacryl Quick Drying Waterproofer in an inconspicuous area and allow to dry to determine colour suitability before commencing work. Shade variations may occur between batches. When completing projects requiring multiple tins, please ensure that they are from the same batch number.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Flexacryl Quick Drying Waterproofer, available at www.bostik.com/uk.

PACKAGING

Product codes	30811944	Grey 5L can x 2
---------------	----------	-----------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Sales	Tel: 0844 371 1192	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.