



Bituminous Black Paint

SOLVENT-BASED PROTECTIVE CORROSION RESISTANT PAINT

TECHNICAL SHEET NO: TDS00383 09/01/2026

SMART ADVANTAGES

- Water & weatherproof protective paint
- For metalwork, wood, roofing felt, concrete & cement
- Brush on

DESCRIPTION

Bostik Bituminous Black Paint is a solvent-based, protective paint formulated to provide exceptional waterproofing, weather protection and corrosion resistance for external applications. It is suitable for use on a wide range of substrates, including ferrous and non-ferrous metals, corrugated iron, fibre cement, concrete, cement, roofing felt, and timber. This versatile paint is ideal for protecting gutters, downpipes, railings, gates and corrugated metal sheets against weathering and moisture ingress.

Upon curing, Bostik Bituminous Black Paint forms a durable, odourless, and taint-free black bituminous film that delivers long-lasting protection and performance.



TECHNICAL CHARACTERISTICS

| | |
|--------------------------------|--|
| Colour | Black |
| Form | Low viscosity liquid |
| Specific gravity | 0.9 approx. |
| Composition | A solvent-based bitumen solution |
| Application temperature | +5°C to +30°C |
| Drying time | 4 to 6 hours (depending on coating thickness, ambient temperature and humidity) |

COVERAGE

- Porous surfaces: 4 to 6m² per litre, per coat (approx.)
Non-porous surfaces: 10 to 12m² per litre, per coat (approx.)
(depending on substrate, application technique and performance requirements)

APPLICATION

IMPORTANT: Before using Bostik Bituminous Black Paint, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Ensure the substrate is structurally sound, clean, dry and free from dust, dirt, oil, grease, loose material, rust and other surface contaminants.
- Remove any organic growth i.e., moss or lichen with Bostik Fungicidal Wash and allow to dry.
- Metal surfaces should be wire brushed to remove rust. Metal surfaces with residual rust remaining should be treated with a zinc phosphate, or other suitable rust inhibitive primer.
- Most surfaces do not need to be primed. Highly porous or friable surfaces, or new galvanised sheeting should be primed with Bostik Penetration Primer (see separate product data sheet). Ensure that the primer is fully dry before applying Bostik Bituminous Black Paint.
- Surfaces to be treated must be completely dry and free of water.

APPLICATION

- Stir thoroughly before use. Do not thin or dilute.
- Bostik Bituminous Black Paint is ready for use and does not require thinning.
- Apply at least two coats by brush, allowing each coat to dry (normally 4 to 6 hours) before applying the next.

Non-potable water tanks:

- Apply a minimum of two coats, allowing at least 4 to 6 hours to dry between each coat. This may be longer depending on ambient conditions.
- Thoroughly wash out the tank after the final coat has dried.

CLEANING

- Clean tools and equipment with white spirit immediately after use. Dried product may be removed by soaking in cleanser.

STORAGE

- Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 24 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C, out of direct sunlight and away from sources of heat and ignition. Protect from frost.

PRECAUTIONS IN USE

For external use only.

Do not apply to ponds, fishponds, or swimming pools. Do not apply when the surface is too hot. It is not advisable to work in humid, or foggy weather conditions, or when there is a risk of rain before the paint has dried.

Do not apply over roof lights, glass or windows. Coating clear glass, or clear plastic roofs, or roof-lights might constitute a hazard.

Colour indicated on pack is a guide only. It is recommended that users apply a small amount of Bostik Bituminous Black Paint in an inconspicuous area and allow to dry to determine colour suitability before commencing work. Shade variations may occur between batches. When completing projects requiring multiple tins, please ensure that they are from the same batch number.

The paint may progressively lighten in colour after application. These changes are purely cosmetic and do not affect the protective properties of the coating.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Bituminous Black Paint, available at www.bostik.com/uk.

PACKAGING

| Product codes | | |
|---------------|----------|--------------|
| | 30812217 | 1L tin x 6 |
| | 30618122 | 2.5L tin x 6 |
| | 30812219 | 5L tin x 4 |
| | 30812221 | 22.5L drum |

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625
Sales: customer.service@bostik.com
Technical advice: technical.service@bostik.com
Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.