



Bostik Roll

REINFORCED DOUBLE-SIDED ADHESIVE TAPE

TECHNICAL SHEET NO: TDS01945 08/07/2025

SMART ADVANTAGES

- Solvent-free adhesive tape
- Instant grab
- Clean & easy installation

DESCRIPTION

Bostik Roll is a high strength adhesive tape designed for the fast installation of textile and resilient floor coverings, skirtings, capping strips, coving and other floor or lightweight wall mounted accessories. It can be used as a direct alternative to traditional solvent and water-based adhesives.

The double-sided tape is quick, easy and clean to use, offering an immediate grab with a pressure sensitive bond. Bostik Roll is solvent-free and does not leave behind any vapours often associated with traditional contact adhesives. It will not discolour bonded materials and offers excellent plasticiser migration resistance, making it particularly suited for use with PVC products.

Bostik Roll is available in 4 sizes, enabling complex applications to be carried out.

Bostik Roll is an environmentally friendly option that has little impact on the building occupants. It achieves A+ and EC1 Plus ratings, with LEED and EN 13999 : 2007 for BREEAM, thanks to its very low VOC emissions.



TECHNICAL CHARACTERISTICS

Form	Self-adhesive tape
Composition	Pre-coating based on synthetic resins and reinforced weft
Application temperature	+10°C to +30°C
Open times	Unlimited
Drying times	Ready for immediate use
Foot traffic	Ready for immediate use
Curing times	Ready for immediate use

APPLICATION

All phases of the application should comply with the current editions of:

- BS 8102 Code of practice for protection of below ground structures against water ingress.
- BS 5325 Code of practice for installation of textile floor coverings.
- BS 8203 Code of practice for installation of resilient floor coverings.
- BS 8201 Code of practice for installation of flooring of wood and wood-based panels.

Ensure the correct PPE is worn during use.

PREPARATION

- Ensure the substrate is clean, sound, smooth, dry and free from any contaminants that may hinder adhesion.
- Any contaminants on either the wall or floor that may hinder adhesion, such as and not limited to grease, dust, wallpaper, silicone sealants, some curing compounds and old adhesive residues should be completely removed.
- Metal, plastic, previously applied adhesives, or painted walls will need mechanically abrading to provide a key. If in doubt always carry out a trial to ensure compatibility.
- Ensure any damaged walls or floors are suitably repaired to provide a smooth, flat surface to apply Bostik Roll to.

PRIMING

- Textured and/or porous surfaces must be primed prior to the application of Bostik Roll. Prime the surface with Bostik GRIP A526 UNIVERSAL.
- Dense, compact surfaces should be lightly abraded and made dust free. Prior to the application of Bostik Roll, the surface should be wiped with a damp cloth and left to dry.
- Do not use a solvented, aerosol primer to prime the substrate, (solvented primers may lead to impaired adhesion).

ACCLIMATISATION

- Prior to application, ensure that the installation environment is suitable and stable and not likely to experience significant fluctuation in temperature.
- Ensure the Bostik roll is decanted from the packaging and acclimatised in the installation environment for a minimum of 24 hours prior to application.
- Ensure all PVC accessories are decanted from their packaging and acclimatised in the installation environment a minimum of 24 hours prior to application.
- Ensure all flooring materials are unpackaged from their packaging.
- Cold temperatures and damp sites can result in a condensate of water on the substrates and materials being applied, which will prevent adhesion. Ideal performance will be achieved in the temperature range +10°C and +30°C.

APPLICATION

- Ensure that the surface is suitable for the application, prepared in accordance with the guidance given and if applicable, primed with Bostik GRIP A526 UNIVERSAL.
- In all instances, Bostik Roll must be applied directly to the wall. Bostik Roll should not be applied to the product first.

- Remove the tape release paper and ensure all accessories and floor coverings are firmly placed onto the tape.
- Once firmly in place, roller the materials to enhance the bond.
- Bostik Roll provides an instant pressure sensitive bond enabling further processes to be carried out immediately.
- In areas such as shower enclosures and wet rooms, it is essential that the design ensures water is kept away from the adhesive bond line, and where necessary use a bead of suitable sealant.
- Refer to individual Bostik Roll installation guidance for separate application methods.

STORAGE

- Store and transport securely. Store for up to 18 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +10°C to +30°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

For installations using short individual lengths of PVC accessories in areas where temperature fluctuations are anticipated or possible, the use of a Bostik joint sealing glue is recommended to provide mitigation against dimensional instability of the installed product. We would also recommend using this process where lesser grades of PVC are present or suspected.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Roll, available at www.bostik.com/uk.

PACKAGING

Product codes		
30607844	25mm x 50m	
30607845	50mm x 50m	
30607846	85mm x 50m	
30607857	240mm x 25m	

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625
Sales: customer.service@bostik.com
Technical advice: technical.service@bostik.com
Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.