



Cementone Concrete Mould Oil

RELEASE AGENT FOR SHUTTERING

Date: 19 August 2020

Fact Sheet No.: TDS00535

YOUR SMART ADVANTAGES

- For easy removal of shuttering
- Ideal for timber or metal formwork
- Does not stain concrete

USES

Bostik Concrete Mould Oil is a release agent formulated for application onto timber or metal formwork. It allows concrete shuttering to be easily removed, leaving a clean and well-formed edge to the concrete. The water in oil formulation is supplied ready to use and produces a uniform, stain-free surface.

It is economical to use because it is not absorbed into timber or plywood.

PRODUCT CHARACTERISTICS

Colour	White
Form	Thin liquid
Odour	Oily
Specific Gravity	0.97 approx.
Composition	Water in oil emulsion ("soap oil")
Product Codes	30812506 5 litres x 4 30812505 25 litres
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 24 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from

frost.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+5°C to +25°C
PH	10.5
Coverage	12 – 14m ² per litre (depending on application technique)
Cleaning	Clean tools and equipment with warm soapy water immediately after use

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Concrete Mould Oil, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Shake well before use.

APPLICATION

2. Do not apply Concrete Mould Oil by spray. Do not use on plastic moulds. Do not apply in freezing conditions.
3. Concrete Mould Oil is supplied ready to use. Apply an even coat to timber or metal formwork by brush, sponge or soft broom.
4. For new or unsealed timber, apply several coats before initial use.

CLEANING

5. Clean tools and equipment with warm soapy water immediately after use.

PRECAUTIONS IN USE

Do not apply Bostik Concrete Mould Oil by spray. Do not use on plastic moulds. Never apply in freezing conditions.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Concrete Mould Oil, available at www.bostik.com/uk.



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com