



FIX A760 TECH

ULTRA HIGH PERFORMANCE TACKIFIER ADHESIVE

TECHNICAL SHEET NO: TDS02155 05/12/25

SMART ADVANTAGES

- High performance, permanently tacky film
- Facilitates the easy removal and replacement of floor coverings
- Ideal for all types of absorbent and non-absorbent subfloors including metal and raised access flooring

DESCRIPTION

Bostik FIX A760 TECH is a heavy-duty tackifier adhesive for the application of all types of removable carpet and vinyl tiles, loose-lay LVT & rubber, heterogeneous PVC flooring, underlay and broadloom carpets.

Bostik FIX A760 TECH is a solvent-free, non-staining polymer dispersion adhesive designed to provide a permanently tacky film when dry. This facilitates the easy removal and replacement of the floor covering. It is particularly well suited to office environments and raised access panel systems.

Bostik FIX A760 TECH is suitable for bonding stable, flat carpet tiles backed with PVC, polypropylene and bitumen with fibre backing and loose lay resilient flooring; to raised access floor panels, concrete, cementitious screeds, asphalt, terrazzo, chipboard, hardboard, plywood, smoothing compounds and existing floor coverings, e.g. thermoplastic tiles, PVC or linoleum.

It is suitable for use with warm water underfloor heating systems, provided a surface temperature of +27°C is not exceeded.



TECHNICAL CHARACTERISTICS

Colour	Pink
Form	Liquid
Specific gravity	1.02 approx.
Composition	Water-based acrylic
Application temperature	+10°C to +25°C
Waiting times	Absorbent surfaces: 45-60 minutes (approx.) Non-absorbent surfaces: 1-2 hours (approx.)
Open times	Permanently tacky
Walk on time	Immediately
VOC emissions	Very low emissions EC1

COVERAGE

- Absorbent surfaces: approx. 0.10kg to 0.12kg/m²
- Non-absorbent surfaces: approx. 0.06kg to 0.08kg/m² (depending on the smoothness and absorbency of the subfloor)

APPLICATION

IMPORTANT: Before using Bostik FIX A760 TECH, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

All phases of the application should comply with the current editions of:

- BS 8102 Code of practice for protection of below ground structures against water ingress.
- BS 5325 Code of practice for installation of textile floor coverings.
- BS 8203 Code of practice for installation of resilient floor coverings.
- BS 8201 Code of practice for installation of flooring of wood and wood-based panels.

Ensure the correct PPE is worn during use.

PREPARATION

- Ensure the subfloor is clean, sound and dry (<75%RH), of adequate tensile & compressive strength, free from laitance, cracks, structural defects and contaminants that may prevent adhesion (e.g., dust, oil, grease, paint, plaster, polish, some curing compounds, surface hardeners, additives and adhesive residues must be completely removed), and conforms to BS 8204 code of practice.
- For subfloors that are not sufficiently smooth or require height build-up to receive the particular floor covering, an application of a suitable Bostik smoothing compound and primer system is recommended. Please contact Technical Services for advice on specific products and subfloors.
- The temperature of the floor and application environment must be stable and maintained between +5°C and +25°C throughout the application and drying of the adhesive. Room conditions must be maintained for 24 hours while the adhesive fully cures.

UNDERFLOOR HEATING

- Bostik FIX A760 TECH can be used on substrates containing warm water underfloor heating systems. The system must be switched off 48 hours prior to, during and for 48 hours post application. To prevent rapid dehydration, wait 48 hours after installation before gradually turning up underfloor heating.

PRIMING

- In certain cases, on very absorbent open textured screeds, it may be beneficial to prime the surface using Bostik GRIP A526 UNIVERSAL. Dilute 1 part Bostik GRIP A526 UNIVERSAL to 4 parts clean, cold water. Apply and allow the primer to fully dry (see separate technical data sheet).
- Priming reduces over-absorption of the adhesive and improves workability, coverage and bond strength.

APPLICATION

- Apply using a roller or a brush and work well into porous surfaces. Allow to fully dry to a clear, tacky film.
NOTE: Laying into wet adhesive on metal surfaces will entrap moisture and may cause rusting.
- Lay tiles and press firmly into position. When removal of tiles is necessary, peel up from one corner.

CLEANING

- Clean tools and equipment with warm water immediately after use. Remove any adhesive from the surface of the floor covering with a damp cloth.

STORAGE

- Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +10°C to +25°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik FIX A760 TECH, available at www.bostik.com/uk.

PACKAGING

Product codes		
	30615496	19kg bucket
	30615497	5kg bucket

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625
Sales: customer.service@bostik.com
Technical advice: technical.service@bostik.com
Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.