



FIX A760 TECH

ULTRA HIGH PERFORMANCE TACKIFIER ADHESIVE

Date: 20 October 2022

Fact Sheet No.: TDS02155

YOUR SMART ADVANTAGES

- High, performance, permanently tacky film
- Facilitates the easy removal and replacement of carpet tiles
- Ideal for all types of absorbent and non-absorbent subfloors including metal and raised access flooring

USES

Bostik FIX A760 TECH is a heavy-duty tackifier adhesive for the application of all types of removable carpet and vinyl tiles, loose-lay LVT & rubber, heterogeneous PVC flooring, underlay and broadloom carpets.

Bostik FIX A760 TECH is a solvent-free, non-staining polymer dispersion adhesive designed to provide a permanently tacky film when dry. This facilitates the easy removal and replacement of the floor covering. It is particularly well suited to office environments and raised access panel systems.

Bostik FIX A760 TECH is suitable for bonding stable, flat carpet tiles backed with PVC, polypropylene and bitumen with fibre backing and loose lay resilient flooring; to raised access floor panels, concrete, cementitious screeds, asphalt, terrazzo, chipboard, hardboard, plywood, smoothing compounds and existing floor coverings, e.g. thermoplastic tiles, PVC or linoleum.

It is suitable for use with warm water underfloor heating systems, provided a surface temperature of +27°C is not exceeded.

PRODUCT CHARACTERISTICS

Colour	Pink
--------	------

Form	Liquid
Specific Gravity	1.02g/cm ³
Composition	Acrylic water based
Product Codes	30615497 5kg 30615496 19kg
Storage/Shelf Life	Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 12 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C and out of direct sunlight. Protect from frost.

PERFORMANCE DATA

Application Temperature	+10°C to +25°C
Coverage	Absorbent surfaces: approx. 0.10kg to 0.12kg/m ² Non-absorbent surfaces: approx. 0.6kg to 0.8kg/m ² (depending on the smoothness and absorbency of the subfloor floor)
Waiting Times	Absorbent surfaces: approx.: 45-60 minutes. Non-absorbent surfaces: approx.: 1-2 hours (depending on ambient conditions and subfloor absorbency)

Open Times	Permanently tacky
Drying Times	Foot traffic: immediately
VOC emissions	Very low emissions EC1 Plus
Cleaning	Clean tools and equipment with warm water immediately after use. Dried material can only be removed mechanically

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik FIX A760 TECH, refer to the relevant Health and Safety Data Sheet, available at www.bostik.com/uk

All phases of installation should comply with the latest editions of:

- BS 8102 Code of Practice for protection of structures against water from the ground.
- BS 5325 Code of Practice for installation of textile floor coverings.
- BS 8203 Code of Practice for installation of resilient floor coverings.
- BS 8201 Code of Practice for installations of flooring of timber, timber products and wood based panel products.

Ensure the correct PPE is worn at all times.

PREPARATION

Subfloor:

- Ensure the subfloor is sound, clean and dry and of adequate tensile and compressive strength. Free from loose material, laitance, cracks and structural defects.
- The subfloor should be tested for moisture in accordance with BS 8203:2017 Annex B. A reading of 75%RH or less confirms that the subfloor is satisfactorily dry. For readings above 75%RH a suitable Bostik surface applied damp proof membrane must be used.
- For subfloors that are not sufficiently smooth or require height build-up to receive the chosen floor covering, an application of an appropriate Bostik primer and smoothing compound is recommended. Please contact Technical Services for advice on products selection.
- Surfaces should be thoroughly cleaned and vacuumed. Prime boards and other porous surfaces with either diluted Bostik Screedmaster Universal Primer (2 parts water to 1 part primer) and allow to dry. This is of particular importance when applying directly to hardboard, chipboard and plywood substrates.

- Before applying any adhesive, ensure the substrate is dry and dust free.
- It is suitable for use over well-bonded existing PVC and linoleum, ceramic tiles, metal and timber substrates however, ensure all traces of polishes, coatings and contaminants have been removed.

Underfloor heating systems:

- Warm water underfloor heating systems must be switched off for 48 hours prior to, during and for a minimum of 48 hours after application. After this time, gradually turn up the underfloor heating until operational temperature has been achieved.

APPLICATION

- Apply using a roller or brush and work well into porous surfaces. Allow to fully dry to a clear tacky film.
NOTE: Laying into wet adhesive on metal surfaces will entrap moisture and may cause rusting.
- Lay tiles and press firmly into position. When removal of tiles is necessary, peel up from one corner.

CLEANING

- Clean tools and equipment with warm water immediately after use. Remove any adhesive from the surface of the floor covering with a damp cloth. Dried material can only be removed mechanically.

PRECAUTIONS IN USE

For any application not covered, please contact Technical Services on +44 (0) 1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik FIX A320 TACK, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com