



Flashband Primer S.V.

PRIMER FOR BOSTIK FLASHBAND

TECHNICAL SHEET NO: TDS00039 28/10/2025

SMART ADVANTAGES

- Quick dry, cold weather formulation
- Improves grab and adhesion for Flashband flashing tape
- For porous, rough, dusty or damp surfaces

DESCRIPTION

Bostik Flashband Primer S.V. is a solvent-borne bitumen solution designed to prepare porous or dusty surfaces before applying Bostik Flashband, especially in damp or cold weather. It is also suitable for priming smooth, non-porous surfaces. It primes and seals brickwork, cement renderings, roof tiles, concrete, mineralised felt, timber, metal, metal rainwater pipes & gutters and corrugated sheeting.

Its fast drying, easy application formulation makes it ideal for cold, damp conditions.

It is also ideal to use prior to the application of other bitumen products and particularly where there are porous or dusty surfaces.



TECHNICAL CHARACTERISTICS

Colour	Black
Form	Thin liquid
Specific gravity	0.86 approx.
Composition	Solvent-borne bituminous solution
Application temperature	+5°C to +30°C
Service temperature	-10°C to +65°C (depending on operating conditions)
Drying time	2 to 6 hours (depending on coating thickness, ambient temperature and humidity)

COVERAGE

- 4 to 6m² per litre (approx.)
(depending on substrate, application technique and performance requirements)

APPLICATION

IMPORTANT: Before using Bostik Flashband Primer S.V., refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Ensure the roof surface is structurally sound, clean, dry and free, as far as possible from dust, dirt, oil, grease, loose material, rust, paint and other surface contaminants.
- Remove any organic growth i.e., moss or lichen with Bostik Fungicidal Wash and allow to dry.
- New metal surfaces should be degreased with a suitable solvent. Metal surfaces should be wire brushed to remove loose dust or rust. Surfaces with residual rust remaining after cleaning should be treated with a zinc phosphate or other suitable rust inhibitive primer.
- Gaps, deep hollows and depressions greater than 3mm should be filled with an appropriate filler.

APPLICATION

- Stir thoroughly before use. Do not thin or dilute.
- Apply a thin, even coating of Bostik Flashband Primer S.V. to the area where Bostik Flashband is to be applied.
- Apply with a soft bristle brush, brushing it well into the surface. Ensure that only a thin coat is applied and that there is no pooling. Where possible, we recommend using disposable brushes for the application of Bostik Flashband Primer S.V.
- With fibre cement or old roofing felts, apply generously to saturate the surface.
- Allow Bostik Flashband Primer S.V. to dry before applying Bostik Flashband or other bitumen products. However, do not leave applied Bostik Flashband Primer S.V. for more than 24 hours before applying Bostik Flashband. Therefore, only coat an area sufficient for covering within the working day.
- Apply Bostik Flashband to the primed area.

CLEANING

- Clean tools and equipment with white spirit immediately after use. Dried product is difficult to remove.

STORAGE

- Store and transport securely in an upright position. Ensure the lid is secure. Store for up to 24 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C, out of direct sunlight and away from sources of heat and ignition. Protect from frost.

PRECAUTIONS IN USE

For external use only.

Do not use over tar-based products. Do not use if the surface temperature is likely to rise above +65°C. Do not allow the primer to be applied on or near to silicone sealants, or where future solvent contact is likely.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Flashband Primer S.V., available at www.bostik.com/uk.

PACKAGING

Product codes		
	30812257	500ml tins x 12
	30812258	1 litre tins x 12

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625
Sales: customer.service@bostik.com
Technical advice: technical.service@bostik.com
Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.