



Cementone Pave Seal

FAST DRYING EXTERIOR PAVING PROTECTOR

TECHNICAL SHEET NO: TDS00068 25/10/2024

SMART ADVANTAGES

- Clear drying, deep penetration protection
- Resists water, oil and grease
- Enhances the colour of paving

DESCRIPTION

Bostik Pave Seal is a high performance, low viscosity, solvent-based acrylic solution that penetrates deeply into dry, porous external paving such as concrete, brick and porous tiles. It provides excellent resistance to water, oil, petrol, grease and dirt. It is clear in colour, but may enhance the colour of the treated surface.

Bostik Pave Seal is suitable for use to protect drives, paths, patios and other porous exterior paved surfaces.



TECHNICAL CHARACTERISTICS

Colour	Transparent, dries to a matt satin finish
Form	Thin, solvent-based liquid
Specific gravity	0.9 approx.
Composition	Solvent-based acrylic resin solution
Application temperature	+5°C to +25°C
Drying time	Foot traffic: 4 hours approx. Vehicular traffic: 24 hours approx. (depending on coating thickness, surface porosity, weather conditions and drying conditions)

COVERAGE

- 5m² to 8m² per litre, per coat
(depending on porosity of surface and application technique)

APPLICATION

IMPORTANT: Before using Bostik Pave Seal, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- The surfaces to be treated must be clean, dry and free from oil, dust, grease, stains, moss and loose materials.
- Remove any efflorescence from surfaces using Bostik Brick & Patio Cleaner, as directed. Rinse thoroughly and allow to dry completely, not just at the surface, for at least 48 hours before application of Bostik Pave Seal. Do not use detergents to wash surfaces.
- New cement-based surfaces should be allowed to cure for at least 28 days after laying, before application.
- Do not apply to non-porous materials e.g., quarry tiles, wet moulded concrete slabs, patterned/imprinted concrete, some dense bricks, or to natural stone.
- Work must be carried out in dry weather within the temperature range +5°C to +25°C. Do not apply in wet or frosty conditions.
- Always test on a small, inconspicuous area first and allow to fully dry before proceeding to full application. The test area should be examined after 24 hours to safeguard against any unwanted changes of appearance to surfaces and to ensure that the finish is acceptable. The surface appearance will vary due to different paving compositions and colours.
- Cover windows, doors, plants, ponds and surrounding surfaces with plastic sheeting prior to application. Ensure there is good ventilation.

APPLICATION

- Shake well before use. Do not thin or dilute.
- Animals and children must be kept away from the treatment area during application and until the area is completely dry and free of any residual product.
- Bostik Pave Seal must only be applied to dry, porous, exterior floor surfaces which are above ground level. If applied to wet or non-porous surfaces, it will leave a white deposit, which is very difficult to remove.
- Ensure there is good ventilation prior to use. Do not apply in very cold or wet conditions.
- Apply evenly using a soft brush, roller or spray. Work into the surface, but do not allow to pool. Remove excess product from the surface immediately.
- After 2 to 3 hours, apply second coat. A third coat may be required on very porous surfaces.
- Splashes on glass or metal parts must be removed immediately.
- Do not walk on the applied surface until the product is completely dry, as any marks will be difficult to remove.
- Protect freshly applied product from rain and frost until dry.
- Leave surfaces to dry completely before use – approx. 4 hours for foot traffic and 24 hours for vehicular traffic, depending on ambient conditions and the number of coats.

CLEANING

- Clean tools and equipment with white spirit immediately after use. Remove splashes before they have dried.

- Dried product and product splashed onto porous surfaces is difficult to remove.
- Bostik Pave Seal helps resist staining, however, any spillages must still be cleaned up as soon as possible.

STORAGE

- Store and transport securely in an upright position. Ensure the cap is fully closed. Store for up to 24 months from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +25°C, out of direct sunlight and away from sources of ignition. Protect from frost.

PRECAUTIONS IN USE

Due to the solvent content, do not use indoors or in enclosed areas. Do not apply to walls; this product is designed for application to external paving only. Bostik Pave Seal must not be used internally or in enclosed areas where the lingering odour of solvent may be a problem. Efflorescence may still occur after application of Bostik Pave Seal. Do not apply to patterned/imprinted concrete. Do not use around swimming pools, or for waterproofing ponds and pools. Take care to prevent run-off getting into nearby pools or ponds. Do not use acid cleaners to clean the paving once Bostik Pave Seal has been applied.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Pave Seal, available at www.bostik.com/uk.

PACKAGING

Product codes	30812235	5L tins x 4
----------------------	----------	-------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone: 01785 272625
Sales: customer.service@bostik.com
Technical advice: technical.service@bostik.com
Safety data sheets: sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.