



# W110

## BUTYL ALUMINIUM ACOUSTIC WRAP

TECHNICAL SHEET NO: TDS01916 27/03/2024

### SMART ADVANTAGES

- Acoustic tested to BS EN ISO 10140-2
- Fire tested
- Self-adhesive, meaning quick & easy application

### DESCRIPTION

Bostik W110 Acoustic Wrap is a self-adhesive membrane supplied on a compact and lightweight roll. It's designed for use on plastic rainwater & soil pipes where temperatures do not exceed +90°C. It adheres to many common building materials such as PVC & steelwork.

Bostik W110 is supplied ready to use and does not require time to cure or dry and forms an instant bond around pipework. The butyl adhesive is moisture resistant. It is very thin and can be used in tight applications ensuring less room is taken up on site.

No extra banding is required saving installation time and materials on site. It is independently fire and acoustic tested to ensure highest product performance.

Bostik W110 consists of an acoustic layer laminated between two layers of high-performance pressure sensitive butyl and finished with an aluminium face. The compact and lightweight roll is easy and safe to move around site.



### TECHNICAL CHARACTERISTICS

<b>Colour</b>	Aluminium finish
<b>Composition</b>	Aluminium film / butyl adhesive / PP foam / butyl adhesive
<b>Standard thickness</b>	4.5mm ± 20%
<b>Weight per m<sup>2</sup></b>	2.5kg approx.
<b>Application temperature</b>	+5°C to +40°C
<b>Service temperature</b>	-30°C to +90°C (depending on operating conditions)
<b>Fire tests</b>	Independently tested to EN ISO 11925-2  Reaction to fire classification according to EN 13501-1: E / E <sub>FL</sub> / E <sub>L</sub>  ISO 11925-2 test was performed with the W110 applied onto 25-micron aluminium foil with the edges sealed with 50mm T303 Self-Adhesive Aluminium Foil Tape. Edges must be sealed to obtain the class E rating  Independently tested to BS476 - Part 7: Class 1

	BS476 – Part 7 test was performed with product applied to 3mm PVC sheeting. Results may vary when applied onto other substrates
<b>Acoustic performance</b>	Independently tested in accordance with BS EN ISO 10140-2. Weighted sound reduction index ( $R_w$ ) and spectrum adaption terms ( $C$ and $C_{tr}$ ) were derived in accordance with BS EN ISO 717  $R_w (C;C_{tr}) = 25$ dB when applied to 3mm PVC sheeting. Results will vary when applied onto other substrates

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik W110 Acoustic Wrap, available at [www.bostik.com/uk](http://www.bostik.com/uk).

#### PACKAGING

<b>Product codes</b>	30623322	Rolls of 4.5m x 50cm
----------------------	----------	----------------------

#### APPLICATION

**IMPORTANT:** Before using Bostik W110 Acoustic Wrap, refer to the relevant Health & Safety Data Sheet, available at [www.bostik.com/uk](http://www.bostik.com/uk).

#### PREPARATION

- The surface to be bonded must be clean, dry and free from dust, grease and loose materials.

#### APPLICATION

- Unwind the roll and cut a piece to the size required to wrap around the pipe, ensure a minimum 25mm overlap. Start to peel off the protective liner taking care not to touch the adhesive surface. Align the wrap over surface and attach to the surface. While removing the protective liner progressively pull the wrap taut and then press down well over the entire surface.
- To avoid air bubbles, carry out roll-pressing to achieve a good adhesive bond. Ensure that the overlap is well adhered.
- Use Bostik T303 Self-Adhesive Aluminium Foil Tape to seal all the joints.

#### STORAGE

- Store for up to 2 years from date of manufacture in original, unopened packaging in cool, dry conditions within the temperature range +5°C to +30°C and out of direct sunlight. Protect from frost. Storage above +50°C may lead to difficulties in removing the release liner when applying.

#### PRECAUTIONS IN USE

The person carrying out the building work should arrange for sound insulation testing to be carried out by a test body with appropriate third-party accreditation. Approved Document E, sections 2, 3, 4 and 6 give examples of constructions which if built correctly should achieve the sound insulation values for dwelling houses and flats. The guidance in these sections is not exhaustive and other designs, materials or products may be used to achieve the required performance.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit [www.bostik.com/uk](http://www.bostik.com/uk) for advice.

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Sales	Tel: 0844 371 1192	<a href="mailto:customer.service@bostik.com">customer.service@bostik.com</a>
Technical Advice	Tel: 0844 371 1197	<a href="mailto:technical.service@bostik.com">technical.service@bostik.com</a>
Safety Data Sheets	Tel: 01785 272625	<a href="mailto:sds.box-eu@bostik.com">sds.box-eu@bostik.com</a>

#### DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

**Bostik Ltd**  
Common Road,  
Stafford, ST16 3EH, UK  
Phone: +44 (0)1785 272625  
[www.bostik.com/uk](http://www.bostik.com/uk)

**BOSTIK HOTLINE**

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.