



◀ **Learn more**  
about Bostik's  
commitment to our  
customers and our  
global community.

# SUSTAINABILITY BEGINS WITH A STRONG FOUNDATION.

A dedication to responsible living is something we all should embrace. For Bostik, it means creating **sustainable building construction solutions**.

Bostik offers a portfolio of sustainable products that deliver quality through strength and science. With a customer-focused approach and a commitment to a more sustainable world, Bostik continues to deliver innovative solutions that are backed by industry-leading warranties.

At Bostik, we strive for quality—quality in our products, quality in service, **quality in life**.



**BOSTIK**

# A COMPREHENSIVE PORTFOLIO OF SUSTAINABILITY.

Our construction solutions offer a variety of elements that contribute to **sustainable living**, including LEED® and WELL Building Standard project certifications.



Reduced emissions of VOCs and formaldehyde promote good indoor air quality



Recyclable product packaging



Pre-mixed grout does not require water in the mixture, and they can be cleaned in one step



Materials that use bio-based and sustainable harvesting practices



Locally-sourced materials, and production plants built near raw material feedstocks



Moisture-blocking technology that can help prevent damage or degraded applications



Pre-mixed grouts and crumb rubber thickness control spacers use both pre-consumer and post-consumer recycled content



Extended shelf life to prematurely avoid landfill waste



A “red-list free” strategy in formulation efforts helps avoid toxic compounds



Better insulation value in terms of better sound reduction from impact or sound transmission



Product installations that can last as long as 75 years\*



Primers that facilitate installation over existing floors, avoiding demolition costs and unnecessary waste



Contributor to United Nations Sustainable Development Goals

**ACCESS THE INFORMATION YOU NEED FOR YOUR PROJECT ON DEMAND AT [BOSTIK.COM/SUSTAINABILITY](https://www.bostik.com/sustainability)**

\*Products and product installations can last up to 75 years for tile applications.



		<b>IW-EPD</b> 	<b>PS-EPD*</b> 	<b>HPD*</b> 	<b>FloorScore**</b> 
	<b>Product Name</b>				
Caulks and Sealants	<b>Pure Silicone™</b> 100% Neutral-Cure Silicone		✓	✓	
	<b>PRO-MS 50™</b> Silyl-Modified Polyether Construction Sealant & Adhesive		✓	✓	✓
	<b>915FS™</b> Fast Setting Polyurethane Sealant & Adhesive		✓	✓	
	<b>Grip N Grab™</b> Advanced Hybrid Polymer Grab Adhesive		✓	✓	✓
Grouts	<b>Hydroment® Vivid™</b> Rapid Curing High Performance Grout	✓	✓	✓	✓
	<b>TruColor® RapidCure™</b> Premium, Pre-Mixed, Urethane Grout		✓	✓	✓
	<b>Dimension® RapidCure™</b> Glass-Filled, Pre-Mixed, Urethane Grout		✓	✓	✓
	<b>EzPoxy™ EzClean™</b> 100% Solids Epoxy Mortar & Grout		✓	✓	
Hardwood Adhesives	<b>Bostik's BEST®</b> Wood Flooring Urethane Adhesive and Moisture Vapor Control		✓	✓	✓
	<b>GREENFORCE®</b> Advanced Tri-Linking™ Adhesive and Moisture Control Membrane		✓	✓	✓
	<b>Ultra-Set® SingleStep2™</b> Advanced Tri-Linking™ Adhesive, Moisture Control & Sound Reduction Membrane		✓	✓	✓
	<b>Vapor-Lock™</b> Hardwood Adhesive, Moisture Control & Sound Reduction Membrane		✓	✓	✓
	<b>Wood-Tack™</b> Engineered Wood Flooring Adhesive				✓
Moisture Mitigation and Waterproofing	<b>Roll-Cote™</b> High-Performance Moisture Vapor Barrier Coating and Primer		✓	✓	✓
	<b>Slab-Cote™</b> Extreme Moisture Vapor Barrier Coating		✓	✓	✓
	<b>GoldPlus™</b> Latex Waterproofing and Anti-Fracture Membrane		✓	✓	✓
Mortars and Thin Sets	<b>BAM™</b> Fiber-Reinforced, RapidCure™, Large & Heavy Tile Mortar	✓	✓	✓	✓
	<b>Big Tile &amp; Stone™</b> Polymer-Modified Large & Heavy Tile Mortar	✓	✓	✓	✓
	<b>Bostik PM™</b> Multi-Purpose Polymer-Modified Thin Set Mortar	✓	✓	✓	✓
Primers	<b>Universal Primer™ Pro</b> Deep Penetrating Primer		✓	✓	✓
Resilient Adhesives	<b>LOCK A100 COVE™</b> Cove Base and Wall Adhesive				✓
	<b>LOCK A285 MP™</b> Contractor Grade Multi-Purpose Adhesive				✓
	<b>LOCK A490 LVT™</b> Firm-set Vinyl Flooring Adhesive				✓
	<b>LOCK A495 AERO™</b> Solvent Free Aerosol Resilient Adhesive				✓
	<b>LOCK A499 PSA™</b> Universal Pressure-Sensitive Adhesive				✓
	<b>LOCK A699 PSA™</b> High-Moisture Resistant Resilient Adhesive				✓
	<b>LOCK A799 TRANSITIONAL™</b> Universal Firm-Set Transitional Adhesive				✓
Specialty Adhesives	<b>Bosti-Set™</b> Thin Porcelain Tile Panel Adhesive & Sound Reduction Membrane		✓	✓	✓
Substrate Preparation	<b>COTE A985 ENCAPSULATOR™</b> Adhesive Residue Encapsulator				✓
	<b>COTE A985 GYP™</b> Primer for Alkaline or Porous Substrates				✓
Surface Preparation	<b>SL-100™</b> Self-Leveling Underlayment		✓	✓	✓
	<b>SL-175™</b> Premium Self-Leveling Underlayment & Wear Layer		✓	✓	✓
	<b>UltraFinish™ Pro</b> Premium Portland Cement Repair Patch		✓	✓	✓
	<b>Webcrete® 95</b> Fast-Setting, High Strength, Floor Patch		✓	✓	

\*Eligible for 1.5 LEED® credits.  
\*\*Eligible for 1.0 LEED® credit.



Using a framework developed by our parent company Arkema, we systematically evaluate our adhesive solutions so that a great percentage contributes to the emergence of a more circular economy, and a world that is more sustainable. Learn more about Arkema's ever-growing commitment to sustainability.



**Bostik, Inc.**

11320 W. Watertown Plank Road

Wauwatosa, WI 53226

[www.bostik.com/us](http://www.bostik.com/us)

B32650\_051524

**BOSTIK HOTLINE**

**Smart help 1-800-726-7845**



**Legal Disclaimer:** All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.