





URETHANE ACRYLIC SEALANT & ADHESIVE

Bostik Finant adhesives

KEY FEATURES

- Interior and exterior use
- Weatherproof and mildew resistant
- Available in 145+ colors, including clear

DESCRIPTION

Bostik DUO-SIL[®] is a special formulation of urethane and acrylic emulsion which can be used as an adhesive or caulking compound for commercial and residential construction.

DUO-SIL® as a sealant can be used on vinyl, aluminum and fiber cement siding, windows, doors, brick molding, counter tops, showers and most areas where a sealant is needed.

DUO-SIL® as an adhesive has superior bond to most building substrates with no need for primer. DUO-SIL® will adhere to wood, metal, gypsum board, vinyl, PVC, cove base, molding, foam board and many more building products.

PRODUCT FEATURES

- Easy to apply
- Excellent adhesion to most common building substrates
- · Available in 145+ industry colors, including clear
- Mildew resistant
- Flexible
- · Paintable after 1-2 hours
- Low VOC
- Will not crack or fade
- · Non-hazardous and non-flammable

APPLICABLE STANDARDS

 $\mathsf{DUO}\text{-}\mathsf{SIL}^{\texttt{®}}$ meets or exceeds the standard specification for latex sealants <code>ASTM</code> <code>C834-00</code>, <code>Type</code> <code>C</code>, <code>Grade</code> <code>O^o</code> <code>C</code>.

PACKAGING

Available in 10.1 fl oz (300 ml) cartridges – 12 per case. 140 cases per pallet.

Available in 20 fl oz (591ml) sausages, white only – 12 per case. 45 cases per pallet.









APPROXIMATE COVERAGE CHART Coverage for 10.1 fl oz (300 ml) Cartridge

Depth	Width			
	1⁄8"	1⁄4"	3/8"	1⁄2"
1⁄8"	99	49	33	24
1/4"	—	24	20	12
%"	—	—	11	8
1/2"	_	_	_	6
Lincor Foot nor 101 fl or Contrideo				

Linear Feet per 10.1 fl oz Cartridge



For more information, contact us at:

1-800-359-6398 | www.bostik.com/us