



EvoFlex

**NON-LIPPING TILE ADHESIVE
FOR LARGE FORMAT TILES**

Description

Superior high polymer modified tile adhesive. With in-built **“Evo-Lastic” Technology** making it perfect for laying heavy large tiles.

AS ISO 13007 CLASSIFICATION

- C2 Improved Adhesive (excellent bond)
- S2 Highly deformable (flexible)
- E Extended open time (>30 minutes)
- T Slip resistant

Features

- Superb non-lipping
- Smooth trowel feel
- Strong grab
- Excellent bond
- Long adjustment time
- Early grouting (6-8 hours)
- All rounder, no additive required
- Single component, 2 pack performance

Recommended Use

- Perfect for heavy large format tiles
- High traffic
- Where superior bond is needed
- When one adhesive is needed for most jobs



Evoflex



SUITABLE FOR

Concrete	Render and early age (green) screeds
Fibre cement, plasterboard	Heated concrete slabs
Bostik compatible waterproofing membrane	

- All moisture stable tile types including porcelain, ceramic, terracotta, terrazzo and stone.

COVERAGE

When mixed bag yields 18 to 19 litres	
Approximate Coverage (10mm trowel)	
kg per m ²	m ² per bag
2.8	7.0

WORKING TIME

POT LIFE	SETTING TIME	OPEN TIME
3Hrs	6 - 8 Hours	>30min

PRODUCT DETAILS

ITEM NO	ITEM NAME	COLOUR	SIZE
30840446	EVOFLEX	OFF WHITE	20KG

IMPORTANT NOTES: This Sell Sheet is not intended as a replacement for the appropriate Technical Data Sheet. Always check the Packaging, Technical Data Sheet and MSDS before using. If there is any doubt contact Bostik before commencing work.

BOSTIK HOTLINE

Smart help
1300 267 845

BOSTIK AUSTRALIA
Level 1, 6 English Street,
Essendon Fields, VIC 3041
www.bostik.com.au



This document supersedes all previously published literature.
April 2019



**V.O.C
COMPLIANT**