



# Excelflex

## TILE ADHESIVE

## Description

A rubber modified, flexible tile adhesive. Well suited to general tiling where flexibility is required. Suitable for domestic and general tiling.



### AS ISO 13007 CLASSIFICATION

- C1 Normal Cementitious Adhesive
- S1 Flexible

## Features

- Flexible
- Versatile all rounder

## Recommended Use

- Best used for general domestic tiling where some flexibility is required
- Suitable substrates include concrete, screed and render, fibre cement, plasterboard and over the top of the Bostik Dampfix range of waterproofing membranes
- Wall and floor compatible
- Use with all moisture stable tiles such as porcelain, ceramic, terracotta, terrazzo, glass and stone



# Excelflex



## SUITABLE FOR

Outdoor and Indoor	Wall and Floor
Screed	Terracotta
Render	Porcelain
Fibre Cement	Mosaic
Plasterboard	Concrete
Bostik Approved Waterproofing Membranes	Moisture Stable Terrazzo and Natural Stone

- Suitable for use with all moisture stable tiles

## COVERAGE

When mixed bag yields 17 to 18 litres	
Approximate Coverage (10mm trowel)	
kg per m <sup>2</sup>	m <sup>2</sup> per bag
2.80	7.0

## WORKING TIME

POT LIFE	SETTING TIME	OPEN TIME
3Hrs	<24hrs	>20min

## PRODUCT DETAILS

ITEM NO	ITEM NAME	COLOUR	SIZE
30840533	Excelflex (NSW)	Off-White	20kg
30840532	Excelflex (WA)	Off-White	20kg

IMPORTANT NOTES: This Sell Sheet is not intended as a replacement for the appropriate Technical Data Sheet. Always check the Packaging, Technical Data Sheet and MSDS before using. If there is any doubt contact Bostik before commencing work.

### BOSTIK HOTLINE

Smart help  
**1300 267 845**

**BOSTIK AUSTRALIA**  
Level 1, 6 English Street,  
Essendon Fields, VIC 3041  
[www.bostik.com.au](http://www.bostik.com.au)



This document supersedes all previously published literature.  
April 2019

