

Megalastic

MULTIPURPOSE CEMENT ADHESIVE

Description

A multi-purpose additive to upgrade the performance of cement based tile adhesives, grouts, screed and other similar systems. Improves adhesion, flexibility and water resistance but maintains workability, open time and pot life. Suitable for outdoors and full immersion once cured.

Features

- Multipurpose
- Suitable for immersed applications
- Improves bond strength
- Improves flexibility

Recommended Use

- Increasing adhesive or grout performance
- Immersed installations
- General purpose additive for cement based systems



Compatible Systems

Upgrade the flexibility, adhesion and water resistance of:

- Cement based adhesives (Except 2 part systems)
- Cement based grouts
- Cement renders
- Cement screeds
- Cement slurry coat primer
- Cement mortars



Megalastic

MIXING

TILE ADHESIVE ADDITIVE: Use undiluted as a total water replacement or follow instructions on adhesive packaging.

TILE GROUT ADDITIVE: Dilute the Megalastic 1:1 with clean water and use this misture instead of water.

SAND/CEMENT SYSTEMS: (e.g. screed, render render or mortar): May be used undiluted or up to 1 part Megalastic to 3 parts water. On site trials may be needed to determine best ratio. Bond to substrate will be improved by treatment with Bostik Multiprime or a slurry coat primer.

SLURRY COAT PRIMER: Mix with approximately equal parts fresh cement (or tile adhesive) and keep agitated. Apply slurry to the surface with a brush as a thin coat. Alow to become touch dry and cover within 72 hours. Cover with polymer modified tile adhesive or Megalastic modified screed.

Do not use Megalastic by itself as a primer.

PRODUCT DETAILS				
ITEM NO	ITEM NAME	COLOUR	SIZE	
30804113	MEGALASTIC	WHITE	20L	

IMPORTANT NOTES: This Sell Sheet is not intended as a replacement for the appropriate Technical Data Sheet. Always check the Packaging, Technical Data Sheet and MSDS before using. If there is any doubt contact Bostik before commencing work.





