



Superfixall

WHITE TILE ADHESIVE

Description

An entry level, off-white tile adhesive for installations with low demand and no flexibility requirements. Can be used in conjunction with Megalastic for improved performance.

AS ISO 13007 CLASSIFICATION

- C1 Normal Cementitious Adhesive
- E Extended open time (>30 minutes)

C2S1E When upgraded with Bostik Megalastic

Features

- Off-white colour
- Extended open time
- Upgradable with Bostik Megalastic

Recommended Use

- Best used for general domestic tiling with ceramic tiles
- Suitable substrates include concrete, screed and render
- When upgraded with Megalastic, suitable substrates include fibre cement and plasterboard and over the top of the Bostik Dampfix range of waterproofing membranes
- Wall and floor compatible
- Use with moisture stable porous backed tiles only such as ceramic and terracotta
- Must be used with Bostik Megalastic when bonding moisture stable non-porous backed tiles such as glass, porcelain, terrazzo or stone



SUITABLE FOR

TILES	Terracotta	Porcelain*
Ceramic		
Natural Stone*	Moisture Stable Terrazzo*	

SUBSTRATES	Render
Screed	Fibre Cement*
Concrete	

Total Immersion* Plasterboard*
Bostik Approved Waterproofing Membranes*
*WHEN MIXED WITH MEGALASTIC

20KG



Superfixall



SUITABLE FOR

Outdoor and Indoor	Wall and Floor
Screed	Terracotta
Render	Porcelain
Fibre Cement	Mosaic
Plasterboard	Concrete
Bostik Approved Waterproofing Membranes	Moisture Stable Terrazzo and Natural Stone

- Suitable for use with all moisture stable tiles when combined with Bostik Megalastic

COVERAGE

When mixed bag yields 14 to 15 litres	
Approximate Coverage (10mm trowel)	
kg per m ²	m ² per bag
3.3	6

WORKING TIME

POT LIFE	SETTING TIME	OPEN TIME
3Hrs	<24hrs	>30min

PRODUCT DETAILS

ITEM NO	ITEM NAME	COLOUR	SIZE
30840259	Superfixall White	Bright White	20kg

IMPORTANT NOTES: This Sell Sheet is not intended as a replacement for the appropriate Technical Data Sheet. Always check the Packaging, Technical Data Sheet and MSDS before using. If there is any doubt contact Bostik before commencing work.

BOSTIK HOTLINE

Smart help
1300 267 845

BOSTIK AUSTRALIA
Level 1, 6 English Street,
Essendon Fields, VIC 3041
www.bostik.com.au



This document supersedes all previously published literature.
April 2019

