

# CRAFT PVA GLUE

# WATER BASED PVA

#### 14 November 2017

### YOUR SMART ADVANTAGES

- Water resistant
- Non staining (once fully cured)
- Mould and fungi resistant once fully cured
- Non-toxic, safe for all the family
- Does not contain food ingredients such as wheat, gluten, flour, egg, nut or milk products

#### **DESCRIPTION**

**Bostik Craft PVA** is a solvent free PVA glue, that is safe, non-toxic and ideal for arts & crafts. Bostik Crfat PVA is a multi purpose glue which will give strong and lasting bond to a variety of porous and semi porous materials.

#### CLASSIFICATIONS/STANDARDS

# **Packaging Only**

Tested in accordance to AS/NZ3 ISO B124:2003 (Safety of Toys – Part 3: Migration of certain elements)

#### USES

Designed to bond a variety of surfaces such as wood, fabrics, leather/suede, felt, sequins, styrene foam, concrete/terracotta and paper. Ideal for models, masks, masonry and other craft work.

PRODUCT CHARACTERISTICS	
Form	Semi thick liquid
Chemical Type	PVA Emulsion
Appearance	White free flowing liquid, slight odour
Viscosity	Approximately 5000 cps
Boiling Point	Approximately 100°C
Specific Gravity	Approximately 1.07
PH Value	4-5
Solids	Approximately 45%

Adhesion	Provides strong adhesion
Cure Time	Full cure approximately 7 days
Solubility in water	Completely dispersible
Product Details 5L White 4pk 236ml White 6pk	30840045 30840345

#### **APPLICATION INSTRUCTIONS**

#### **Surface Preparation**

- Ensure surfaces to be bonded are clean, dry and free from grease, oil dust and other foreign materials.
- 2. Test on small area before use.

#### **Application**

- Apply Bostik Craft PVA glue to one surface and press both surfaces together whilst wet.
- 2. For wood, apply pressure or clamp for 20-30 minutes, longer for joints under stress.
- 3. Maximum strength is reached after 12 hours.
- 4. Clean away excess glue with a moist cloth.
- 5. Clean nozzle and/or replace cap tightly.

#### Removal

To remove from substrates clean away glue with a moist cloth before maximum strength is reached after 12 hours. To remove dried PVA from cloth soak the area with Eucalyptus oil. Test for colourfastness. Then soak in hot water and scrub with a fine brush such as a toothbrush.

## LIMITATIONS

- Not suitable for photographs
- Not suitable for paper restoration

# STORAGE AND SHELF LIFE

Shelf life is 1 year from date of manufacture if stored under dry conditions (away from heat and light) between  $5^{\circ}$ C to  $25^{\circ}$ C. Do not freeze

Bostik Australia Pty Ltd, Level 1, 6 English Street, Essendon Fields, Victoria, 3041, Australia. Tel: +613 9279 9333 www.bostik.com.au

Version 5 Page 1 of 2

# CRAFT PVA GLUE WATER BASED PVA

#### **HEALTH & SAFETY**

Avoid contact with skin and eyes. For more detailed information refer to Material Safety

Data Sheet

#### Potential Allergic Health Effects

**Bostik Craft PVA** DOES NOT contain food ingredients such as wheat, gluten, flour, egg, nut or milk products.

#### First Aid

If swallowed, rinse mouth thoroughly with water immediately. Give 1 or 2 glasses of water to drink and do not induce vomiting.

For eyes, immediately irrigate with copious quantity of water for at least 15 minutes (eyelids to be held open). For skin, wash with plenty of soap and water. In case of emergency, contact 1800 033 111.

#### **PACKAGING**

236mL and 5 Litre jerry can.

#### PRECAUTIONS IN USE

Complete details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that all concerned read the appropriate Safety Data Sheets. Visit www.bostik.com/au for copies.

For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com/au

Bostik Australia Pty Ltd, Level 1, 6 English Street, Essendon Fields, Victoria, 3041, Australia. Tel: +613 9279 9333 www.bostik.com.au

Version 5 Page 2 of 2