

VOC Data Sheet

PRODUCT	PRODUCT NAME		g/Lt	SCAQMD PRODUCT TYPE
30804581	SEAL N FLEX 1 BLACK	300ML	74	ARCHITECTURAL SEALANTS
30803243	SEAL N FLEX 1 GREY	300ML	74	ARCHITECTURAL SEALANTS
30840067	SEAL N FLEX 1 WHITE	300ML	74	ARCHITECTURAL SEALANTS
30804581	SEAL N FLEX 1 BLACK	300ML	74	ARCHITECTURAL SEALANTS
30800511	SEAL N FLEX 1 B/BEIGE	600ML	64	ARCHITECTURAL SEALANTS
30840036	SEAL N FLEX 1 BLACK	600ML	64	ARCHITECTURAL SEALANTS
30840047	SEAL N FLEX 1 BRONZE	600ML	64	ARCHITECTURAL SEALANTS
30604591	SEAL N FLEX 1 CLASS BONE	600ML	64	ARCHITECTURAL SEALANTS
30800959	SEAL N FLEX 1 EPPING GREY	600ML	64	ARCHITECTURAL SEALANTS
30840034	SEAL N FLEX 1 GREY	600ML	64	ARCHITECTURAL SEALANTS
30840037	SEAL N FLEX 1 L/STONE	600ML	64	ARCHITECTURAL SEALANTS
30840052	SEAL N FLEX 1 M/SAND	600ML	64	ARCHITECTURAL SEALANTS
30800963	SEAL N FLEX 1 OFF WHITE	600ML	64	ARCHITECTURAL SEALANTS
30800964	SEAL N FLEX 1 REDWOOD	600ML	64	ARCHITECTURAL SEALANTS
30840046	SEAL N FLEX 1S/STONE	600ML	64	ARCHITECTURAL SEALANTS
30840033	SEAL N FLEX 1 WHITE	600ML	64	ARCHITECTURAL SEALANTS

04/12/2017

Unless otherwise stated, the TVOC of this product has been calculated theoretically, based on the known VOC values of the individual raw material components. In the event that the VOC level of any individual raw material component is unknown, the TVOC has been determined experimentally using SCAQMD Method 304-91, as referenced by the South Coast Air Quality Management District (SCAQMD) Rule 1168.

Sugan Naidoo Technical Director

Note:

For any further enquires contact Bostik on (03) 9279 9333 or voccertificates.australia@bostik.com. A VOC level of "0" is a true value. The VOC level of a product which may be available in a range of colours may vary depending on the colour.

Head Office: Bostik Australia Pty Ltd, Level 1, 6 English St, Essendon Fields, Vic 3041

ABN 79 003 893 838

Tel: 1800 267 845 Fax: 1300 723 688

www.bostik.com.au

A company of ARKEMA