



**DECLARATION OF PERFORMANCE**  
according to Annex III of the Regulation (EU) No 305/2011

Product name:  
**Niboplan Best**  
DoP-Nr. **13813-14-06**

---

1. Unique identification code of the product-type:

EN 13813:2003: **CT-C30-F7-A15-B2.0**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: see packaging of the product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Cement based levelling compound for indoor flooring**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Bostik GmbH, An der Bundesstraße 16, 33829 Borgholzhausen**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3 (The standard requires only system 4)  
CWFT for the reaction to fire**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**A notified testing laboratory, the MPA Braunschweig, NB 0761,  
has performed the determination of the product-type  
on the basis of Initial Type Testing (ITT) under system 3  
and issued the following: Test report, Document-No. (1208/211/14)**

**With reference to the decision 2010/85/EU CWFT for the reaction-to-fire**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance

Essential Characteristic	Performance	Harmonized technical specification
Reaction to fire	E*	EN 13813:2003
Release of corrosive substances	CT	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	C30	
Flexural strength	F7	
Wear resistance	A15	
Wear resistance	NPD	
Tensile adhesion strength on concrete	B2.0	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Dangerous substances	NPD	

\*With reference to the commission's decision 2010/85/EU of Feb. 2, 2010, the product meets fire class E without further testing.

10. The performance of the product identified under point 1. and 2. is in conformity with the performance declared in section 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified under point 4.

Signed for and on behalf of Bostik GmbH by Company Management



Borgholzhausen, 9. Juli 2014

Managing Director (MD)

**Bostik GmbH**

An der Bundesstraße 16, 33829 Borgholzhausen, Germany, Postfach 1154, 33825 Borgholzhausen, Germany

Phone: + 49 (0) 5425 801-0, Fax: + 49 (0) 5425 801-140, E-mail: info.germany@bostik.com

Amtsgericht Gütersloh HRB 4939, Geschäftsführer: Roland Albers, Olaf Memmen

Hypo Vereinsbank, BIC HYVEDEMM488, IBAN DE97 1002 0890 0355 2397 64

A company of TOTAL

[www.bostik.de](http://www.bostik.de)