



DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Product name:

Niboplan U

DoP-Nr. **13813-13-6**

1. Product classification code:

EN 13813: CT-C25-F6-B1,0

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch-No.: see product packaging/labeling

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Cementitious screed material for indoor use in buildings

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Bostik GmbH, An der Bundesstraße 16, D-33829 Borgholzhausen

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

System 3 for the reaction-to-fire

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

A notified testing laboratory, the MPA Braunschweig, NB 0761, has performed the determination of the product-type on the basis of Initial Type Testing (ITT) under system 3 and has issued the following:

Test Report, document-no. 1669/544/07-a

The same notified Body has tested the reaction-to-fire and has in compliance with DIN EN 13501-1 issued the following:

Classification Report K-3753/016/07-MPA BS, class A1_{fl}

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance

Essential Product Features	Performance	Harmonized Technical Specification
Reaction to fire	Class A1 _{fl}	EN 13813:2002
Release of corrosive substances	CT	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	C25	
Flexural strength	F6	
Wear resistance	A22	
Tensile adhesion strength on concrete	B1,0	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Dangerous substances	NPD	

10. The performance of the product identified in section 1 and 2 is in conformity with the performance declared in section 9. This declaration of performance is issued under the sole responsibility of the manufacturer as identified in section 4.

Signed for and on behalf of Bostik GmbH by Company Management



Borgholzhausen, April 15, 2014

Managing Director (MD)

Bostik GmbH

An der Bundesstraße 16, 33829 Borgholzhausen, Germany, Postfach 1154, 33825 Borgholzhausen, Germany

Phone: + 49 (0) 5425 801-0, Fax: + 49 (0) 5425 801-140, E-mail: info.germany@bostik.com

Amtsgericht Gütersloh HRB 4939, Geschäftsführer: Roland Albers, Olaf Memmen

Hypo Vereinsbank, BIC HYVEDEMM488, IBAN DE97 1002 0890 0355 2397 64

A company of TOTAL

www.bostik.de