



# LIQ. 4045

## SOLVENT BASED ADHESIVE

### KEY FEATURES

- Resistant to solvents and plasticizer migration
- Excellent green strength
- Suitable for bonding flexible PVC to a variety of surfaces

### DESCRIPTION

LIQ. 4045 is a fast drying solvent-borne, general purpose nitrile adhesive that exhibits high initial bond strength, nonstaining properties, and a clear flexible film. The high viscosity of this adhesive allows it to be brush or roll applied as well as pre-applied to accommodate a variety of assembly processes. LIQ. 4045 has good resistance to solvents and plasticizer migration.

### PACKAGING


LIQ. 4045 is packaged in pails and drums. Please contact your Bostik representative for additional packaging options.

### SHELF LIFE

The shelf life of LIQ. 4045 is approximately 9 months when stored in the sealed, original container at temperatures of 13°C to 32°C.

### STORAGE & HANDLING

LIQ. 4045 is flammable, so proper safety measures should be taken to avoid ignition of the solvents. Nearby electrical equipment must be rated for use in hazardous environments.



### TYPICAL PHYSICAL PROPERTIES

Description	Results
Appearance	Amber Liquid
Total Solids	26%
Specific Gravity	0.87
Thermosel Viscosity	2,250 cP
Flash Point	-17°C
Heat Resistance	65.6°C
Typical Bond Values, pli	Fabric/ Fabric: 18-20 Fabric/Vinyl: 16-18 Vinyl/Vinyl: 16-18 Vinyl/ABS: 18-22 Vinyl Foam/Solid Vinyl: Foam failure Vinyl/Aluminum: 18-22

The recommended storage temperature range for LIQ. 4045 is 55-90°F (13-32°C). Exposure to colder temperatures can sometimes be reversed by warming the adhesive slowly to room temperature and agitating the material well. Exposure to higher temperatures for a prolonged time can cause premature aging, shortening the shelf life of the product. Viscosity increase caused by heat exposure is irreversible. Do not store LIQ. 4045 in direct sunlight.

### **DILUENT**

MEK or acetone

### **CLEAN-UP**

MEK is recommended for use when small areas need to be cleaned.

### **APPLICATION TECHNIQUES**

Bonding surfaces should be clean and dry. Apply adhesive to one surface and allow to dry. Coat the other surface and while tacky (5 - 7minutes) mate the surfaces together with uniform pressure. Alternatively, coat both surfaces and allow the LIQ. 4045 to dry; the surfaces will be non-tacky. When ready to bond, wipe one surface with MEK and mate surfaces immediately with uniform pressure.

Coated films that are open to the air for prolonged time can be affected by oxidation. To prevent oxidation, limit air exposure to the film. Store away from direct sunlight, in a cool, dry environment.

### **HEALTH & SAFETY PRECAUTIONS**

The Safety Data Sheet should be consulted for proper handling, clean up and spill containment before use. Keep containers covered to minimize contamination.

### **LIMITED WARRANTY**

Limited Warranty found at [www.bostik.com/uso](http://www.bostik.com/uso) or call 800.726.7845. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. BOSTIK DISCLAIMS ANY LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES TO THE MAXIMUM EXTENT ALLOWED BY LAW. DISCLAIMERS OF IMPLIED WARRANTIES MAY NOT BE APPLICABLE TO CERTAIN CLASSES OF BUYERS AND SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO YOU. The information, data, and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. Bostik does not warrant the product's suitability for any particular application. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. The Limited Warranty extends only to the original purchaser and is not transferable or assignable. Any claim for a defective product must be filed within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

#### **BOSTIK HOTLINE**

**Smart help**  
**1-800-726-7845**

**Bostik, Inc.**  
11320 W. Watertown Plank Road  
Wauwatosa, WI 53226  
[www.bostik-us.com](http://www.bostik-us.com)



This document supersedes all previously published literature.  
04.06.2018