



QUELYD EXPRESS

WALL PAPER ADHESIVE WITH HIGH EFFICIENCY

KEY FEATURES

- Ready in to use in 2 minutes
- High efficiency : 6 to 9 rolls
- Easy spreading with brush (long structure)
- Excellent application properties: allows to quickly and easily adjust the wall paper strips
- High dry extract content: bonding security
- Transparent after drying
- Fungicide treatment: avoids mold formation
- Can be reused after 1 week once prepared
- Recommended by major wall paper brands



PRODUCT DESCRIPTION

High efficiency multi-dilution starch adhesive, specially adapted for the installation of wallpapers such as:

- Wallpapers light, standards, thick, heavy
- Wallpapers sponge able and washable
- Single or duplex embossed wallpapers
- Ingrain wallpapers, to paint

TYPICAL PHYSICAL PROPERTIES

CHARACTERISTIC	
Composition	Starch ether based
Appearance	Flakes adhesive, translucent in solution, creamy
Density	0,3
pH in solution	11.0
Adhesive preparation	0 – 2min
Open time	20min
Final strength	24h – 48h
Yield per pack	6 to 9 rolls
Packaging	250 gr

The final strength of the bonding is a function of the temperature and the ambient humidity, the hygrometry and the porosity of the substrates.

Bostik SA
Colombes, France
Phone : +33 (0)1 55 99 90 00
Fax : +33 (0)1 55 99 90 01
www.bostik.com

Bostik Ltd.
Stafford, UK
Phone : +44 (0) 1785 27 27 27
Fax: +44 (0) 1785 22 26 65
www.bostik.com

Bostik GmbH Borgholzhausen,
Germany
Phone: +49 (0)54 25/801140
Fax: +49 (0)54 25/801140
www.bostik.com

Bostik B.V. Benelux
Oosterhout, The Netherlands
Phone: +31 (0)162 491 000
www.bostik.com

Bostik TR
Kimya Sanayi. Istanbul,
Phone: +902826764662
www.bostik.com

SUBSTRATE PREPARATION

The DTU 59.4 "Implementation of wallpapers and wall coverings" defines the professional rules of preparation. It is the responsibility of the applicator to ensure compliance with these rules, as it incurs its responsibility. The DTU 59.4 indicates the maximum degrees of humidity allowed:

- Plaster base: 5%.
- Wood and derivatives: 12% ± 2%.

The below substrate should be flat, smooth, sound, dry permanently (not exposed to rising damp), clean, solid, degreased and dust free, of normal porosity.

Remove old tapestries, whitewashes using our stripper wallpapers and vinyl papers. Eliminate peeling or poorly adhered paints. Scrape old or bright paints with alkaline leach, then rinse.

Sand if necessary, remove dust due to sanding, or apply our primer hanging and let dry for 24 hours minimum.

Fill in the holes or cracks. Fix the friable, floury bottoms with one of our hardeners in alcohol solution or acrylic.

Fill porous bottoms, gypsum plasterboards (plasterboard) with a suitable product.

Prohibit rich, nourishing impressions or mixtures of the "paint residue" type, likely to block the substrate and not compatible with our adhesives.

APPLICATION

Depending on the type of paper, dilute 1 package in a clean bucket with the following amounts of water:

Light wallpapers:

Dilution: 8 liters of water.

Yield: about 8 to 9 rolls, or 40 to 45 m².

Common washable wallpapers:

Dilution: 7 liters of water.

Yield: about 7 to 8 rolls, or 40 m².

Washable, wipeable, thick, embossed, ingrained wallpapers to paint:

Dilution: 6 liters of water.

Yield: about 6 to 7 rolls, or 30 to 35 m².

Shake quickly by creating a vortex, and then pour the contents of the package over the edges of the bucket while continuing to stir.

Maintain gentle stirring for approximately 30 seconds. Let rest for 1 to 2 minutes. Brew vigorously, the adhesive is ready.

Brushing the back of the paper (standard wallpapers, vinyl etc.) Glue the back of the paper sufficiently and regularly with a wallpaper brush. Fold the strip in "wallet" overloading the edges in order to avoid premature drying of the glue on the edges. The "nervous" papers will have to be wrapped in order to annihilate their "nervousness". Respect a tempera time of 5 to 10 minutes according to the thickness of the paper and manufacturer's instructions. The observed

time will be identical throughout the application. Apply the first strip, having taken care to check the plumb. The following lanes will be positioned edge to edge, according to the manufacturer's advice and the order established during cutting. Carefully rub with a broomstick or plastic spatula, from top to bottom and from the center to the edges. Fresh glue stains will be removed immediately with a clean damp sponge.

MISCELLANEOUS REMARKS

We recommend the use of our "DERMOSAFE HAND PROTECTION" product before starting the works: "DERMOSAFE HAND PROTECTION" is a non-greasy cream, which forms a screen against the penetration of Products in the skin and facilitates cleaning of the hands. Cleaning fresh stains with water.

COVERAGE

6 to 9 rolls with 1 box of 250gr

PACKAGING

250gr per box

STORAGE

2 years in unopened packaging and in a dry environment, between 10°C and 20°C.

Above 8 days for the storage of prepared adhesive, in closed container and frost-free.

FURTHER INFORMATION

The following publication is available on request: Material Safety Data Sheets (MSDS)

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

SMART HELP

Please contact your local representative

Bostik SA
Colombes, France
Phone : +33 (0)1 55 99 90 00
Fax : +33 (0)1 55 99 90 01
www.bostik.com

Bostik Ltd.
Stafford, UK
Phone : +44 (0) 1785 27 27 27
Fax: +44 (0) 1785 22 26 65
www.bostik.com

Bostik GmbH Borgholzhausen,
Germany
Phone: +49 (0)54 25/801140
Fax: +49 (0)54 25/801140
www.bostik.com

Bostik B.V. Benelux
Oosterhout, The Netherlands
Phone: +31 (0)162 491 000
www.bostik.com

Bostik TR
Kimya Sanayi. Istanbul,
Phone: +902826764662
www.bostik.com