

FIX A570 MULTI TACK

TACKIFIER ADHESIVE FOR ALL TYPES OF REMOVABLE SOFT TILES

KEY BENEFITS

- High-performance, permanent grab
- All types of removable tiles
- All types of absorbent or non-absorbent subfloors
- Resistant to castor wheels and traffic
- Suitable in new constructions and renovation



APPLICATIONS

DESTINATION

FIX A570 MULTI TACK is an acrylic adhesive suitable for securing textiles and carpets with non-woven backings, such as: Ultratex, Comfort, Duo soft.

Associated floor coverings :

- Carpet tiles (bitumen, PVC backed textile, vinyl)
- Fitted carpets with felt backing
- Subfloors of concrete
- Onto sand/cement screed
- Anhydrite screeds
- Smoothing underlayments
- Flooring grade plywood and timber
- Old PVC
- Tile flooring

Recommended by main manufacturers.
For interior use only.

PRODUCT CHARACTERISTICS

Composition / colour	Acrylic emulsion, solvent-free / white
Waiting time*	Approx. 45 to 60 minutes, subject to ambient conditions.
Open time*	No limit (If dust free)
Walk on time*	Approx. 12 hours for PVC tiles, and immediate for carpets tiles with non-woven backings.
Coverage	40-100g/m ²
Application temperature	Preferably between +10°C and +30°C

*these times are determined at + 23° C and 50 % relative humidity on normally absorbent substrates

SUBFLOOR PREPARATION

CLEANING PREPARATION

Preparation should be in accordance with building standards. Subfloors must be sound, even, smooth, permanently dry and free from old adhesive residues, dust, grease or other contaminants.

Remove dirt, polish, oil and similar contaminating substances.

When further preparation of the subfloor is required, select suitable Bostik primers and Bostik smoothing and levelling compounds.

All surfaces must incorporate adequate damp proofing, if not, they should be primed with HYTEC E336 XTREM Moisture Vapor Barrier coating.

Always allow primers and underlayment to dry thoroughly before applying the adhesive.

METHOD OF USE

Apply an even coat over the whole area to be covered using a foam roller or a notched trowel. Can be sprayed undiluted onto special technical floors. Avoid puddle formation.

In order to replace the tiles it is essential to observe an appropriate waiting time: approx. 45 to 60 minutes, depending on temperature and humidity conditions; substrate absorbency and type of floor covering. On impervious substrates tack time must be at least 4 hours.

BOSTIK FIX A570 MULTI TACK provides a permanent high tack film, tiles are easily replaceable, no additional product needed to uplift tiles.

Press the tiles or carpet firmly in place from the center outwards, paying particular attention to the edges.

Floor covering removal

Uplift the covering starting from a corner and peel off slowly. The adhesive residues can be easily removed by 15% alkaline detergent solution diluted in hot water. Soak the remains of the adhesive for approx. 30 minutes until the adhesive re-emulsifies. Remove with a squeegee and floorcloth. Several rinses are needed to get original floor without any tacky surface.

COVERAGE

From 40 to 100g/m² depending on the type of coating and the spatula used.

STORAGE STABILITY

Up to 12 months in the original, unopened container, stored at +10°C and +30°.

CLEANING

Tools should be cleaned with warm water, preferably whilst the adhesive is still wet.

Code	UC	PCB	GENCOD
30615498	15 kg	1	3549212484798

SAFETY

For more details, consult the safety data sheet on <https://bostikdsd.thewerccs.com/default.aspx>

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the pat

BOSTIK SMART SUPPORT

Smart help
+971 4 875 1700

