

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK WOOD P140 FIRST Supercedes Date: 31-Jan-2020 Revision date 31-Jan-2020 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK WOOD P140 FIRST

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.

Uses advised againstNot to be used in production of toys or childcare articles Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA 420 rue d'Estienne d'Orves 92700 Colombes FRANCE

Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

treland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

2.2. Label Elements

Not classified

Signal word

None

Hazard statements

Not classified

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

EUH210 - Safety data sheet available on request

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

Additional information

.

Reserved for industrial and professional use.

BOSTIK WOOD P140 FIRST Supercedes Date: 31-Jan-2020 Revision date 31-Jan-2020 Revision Number 1

2.3. Other Hazards

No information available

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0		5 - <10	Asp. Tox. 1 (H304) (EUH066)		01-2119456810- XXXX
1,3-Bis(isocyanatomethy I) benzene	222-852-4	3634-83-1	0.01 - <0.05	Skin Irrit. 2 (H315) Eye Irrit. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 2 (H330) STOT RE. 1 (H372) STOT SE. 1 (H370) Resp. Sens. 1 (H334)		01-2119946318- 31-XXXX

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Show this safety

data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a doctor.

Supercedes Date: 31-Jan-2020 **Revision Number 1**

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never

give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

No information available. **Symptoms**

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

BOSTIK WOOD P140 FIRST

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Thermal decomposition can lead to release of toxic and corrosive gases/vapours.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. **Personal precautions**

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow to enter into **Environmental precautions**

soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product

and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

BOSTIK WOOD P140 FIRST
Supercedes Date: 31-Jan-2020
Revision Number 1

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink

or smoke when using this product. Wash thoroughly after handling. Take off all

contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing.

7.3. Specific end use(s)

Specific Use(s) Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Limestone	-	TWA: 10 mg/m ³	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³	TWA: 4 mg/m ³
		STEL: 30 mg/m ³	STEL: 30 mg/m ³
		STEL: 12 mg/m ³	STEL: 12 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available.

(PNEC)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Suitable protective clothing. Gloves made of plastic or rubber. Wear protective

Neoprene™ gloves. Rubber gloves.

Respiratory protection Provide adequate ventilation.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearancePaste viscousColourBeige

Supercedes Date: 31-Jan-2020 Revision Number 1

OdourNo information availableOdour thresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point / freezing point
Boiling point / boiling range
Flash point > 100 °C
Evaporation rate
No data available
> 100 °C
No data available

Flammability (solid, gas) Not applicable for liquids .

Flammability Limit in Air

BOSTIK WOOD P140 FIRST

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

No data available Vapour pressure Vapour density No data available Relative density No data available Water solubility Insoluble in water Solubility(ies) No data available Partition coefficient No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity No data available

Dynamic viscosity 45000 - 75000 mPa s Spindle A6 @ 10 rpm @ 23 °C

Explosive propertiesNo data available **Oxidising properties**No data available

9.2. Other information

Solid content (%)

Softening Point

Molecular weight

VOC Content (%)

Density

No information available
No information available
No information available
No information available
1.6 - 1.65 g/cm³
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerisation Hazardous polymerisation may occur.

10.4. Conditions to avoid

Conditions to avoid Keep from freezing.

10.5. Incompatible materials

Supercedes Date: 31-Jan-2020 Revision Number 1

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

BOSTIK WOOD P140 FIRST

products

Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrogen cyanide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

Revision date 31-Jan-2020

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	LD50 > 5000 mg/kg (Rat) (OECD Guideline 401)	LC50 >2000 mg/Kg (Rattus) (OECD 402)	LC50 >5991 mg/m³ (Rat) Aerosol (OECD Guideline 403)
1,3-Bis(isocyanatomethyl) benzene 3634-83-1	=3200 mg/kg (Rattus)	>5000 mg/Kg (Rattus)	0.35 mg/l 4 hours (Rat nose only)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Component Information						
1,3-Bis(isocyanatomethyl) benzene (3634-83-1)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
	Rabbit	Dermal			irritant	

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Component Information
1,3-Bis(isocyanatomethyl) benzene (3634-83-1)

BOSTIK WOOD P140 FIRST Supercedes Date: 31-Jan-2020 Revision date 31-Jan-2020 Revision Number 1

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit				Eye Damage

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Component Information					
1,3-Bis(isocyanatomethyl) benzene (3634-83-1)					
Method	Species	Exposure route	Results		
	Guinea pig	Dermal	sensitising		

Germ cell mutagenicityBased on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity .

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	-	LL50 96 h >1000 mg/L (Oncorhynchus mykiss)	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

Supercedes Date: 31-Jan-2020 Revision Number 1

vPvB. .

Chemical name	PBT and vPvB assessment
1,3-Bis(isocyanatomethyl) benzene	The substance is not PBT / vPvB
3634-83-1	

12.6. Other adverse effects

BOSTIK WOOD P140 FIRST

Other adverse effects No information available.

.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging

Do not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

European Waste Catalogue

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1UN NumberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing GroupNot regulated14.5Environmental hazardsNot applicable

14.6 Special Provisions None

IMDG

14.1 UN numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated

14.5 Marine Pollutant Np 14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

BOSTIK WOOD P140 FIRST Supercedes Date: 31-Jan-2020 Revision date 31-Jan-2020 Revision Number 1

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1	52[b].

52 . Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

Supercedes Date: 31-Jan-2020 Revision Number 1

H318 - Causes serious eye damage

BOSTIK WOOD P140 FIRST

H330 - Fatal if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H370 - Causes damage to organs

H372 - Causes damage to organs through prolonged or repeated exposure

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 31-Jan-2020

Indication of changes

Revision note SDS sections updated, 1, 2, 3, 8, 11, 12, 16.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet