

Declaration of Performance

No.: 40-605-302-01

1. Unique identification code of the product-type:

Plastic-type sealant for facade elements, suitable for indoor use only.

2. Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):

30602639 ACRYL PEINTURE

See on packaging: batch number, date of manufacture and manufacturing center

3. Use or intended use of the construction product in accordance with the applicable harmonized technical specification, as specified by the manufacturer:

Joint sealants for non-structural use between facade elements, for indoor use only.

4. Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):

Société Bostik, le Jade Building — 253 Av du président Wilson — F-93211 La Plaine Saint-Denis Cedex
www.bostik.fr

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):

Not applicable

6. System or systems of Assessment and Verification of Constancy of Performance of the construction product in accordance with Annex V:

Level 4

7. In the case of a declaration of performance for a construction product covered by a harmonized standard:

The manufacturer has determined the product-type on the basis of type tests and factory production control according to system 4.

8. In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:

Not applicable

Plastic-type sealant for facade elements, suitable for indoor use only.

Declaration of Performance

9. Declared performance:

Sealants for facade elements

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	Class F	EN 15651-1: 2012
Release of hazardous substances	See SDS	
Water and air tightness		
Volume loss	≤ 45%	
Resistance to casting	≤ 5 mm	
Adhesion/cohesion, deformation properties under traction after immersion in water (23°C)	≥ 25%	
Sustainability	Compliant	

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and position of company representative

Christian KLOPFENSTEIN
Deputy Director-General

Place and Date

/stamp/

Plastic-type sealant for facade elements, suitable for indoor use only.