

## Declaration of Performance

No.: 40-600-300-01

**1. Unique identification code of the product-type:**

F-type sealant for facade elements EXT-INT class 12.5P

**2. Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):**

30136823 ACRYL S White

30136833 ACRYL S Gray

30136843 ACRYL S Brown

See packaging: batch number, date of manufacture and manufacturing center.

**3. Use or intended use of the construction product in accordance with the applicable harmonized technical specification, as specified by the manufacturer:**

Joint sealants for non-structural use between facade elements, for indoor and outdoor use.

**4. Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):**

Société Bostik, Le Jade Building — 253 Av du président Wilson — F-93211 La Plaine Saint-Denis Cedex  
[www.bostik.fr](http://www.bostik.fr)

**5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):**

Not applicable

**6. System or systems of Assessment and Verification of Constancy of Performance of the construction product in accordance with Annex V:**

Level 3

**7. In the case of a declaration of performance for a construction product covered by a harmonized standard:**

The notified CEBTP laboratory No. 0074 determined the product-type on the basis of type tests according to system 3 and issued the test report.

**8. In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:**

Not applicable

## Declaration of Performance

### 9. Declared performance:

Sealants for facade elements

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	Class E	EN 15651-1: 2012
Release of hazardous substances	See SDS	
Water and air tightness		
Volume loss	≤ 25%	
Resistance to casting	≤ 3 mm	
Adhesion/cohesion, deformation properties under traction after immersion in water (23°C)	≥ 100%	
Adhesion/cohesion, deformation properties under maintained traction after immersion in water (23°C)	NPD	
Adhesion/cohesion, deformation properties under traction at -30°C	NPD	
Adhesion/cohesion, deformation properties under traction at -30°C	NPD	
Sustainability	Compliant	

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by /signature//stamp/

Name and position of company representative

Place and Date