



## Declaration of Performance

No.: 10-364-104-01

1. Unique identification code of the product-type:

CEMENTITIOUS SCREEDS CT — C16 — F4

2. Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):

BOSTIK FLYT 360

See on the packaging: date of manufacture, batch number, manufacturing center

3. Use or intended use of the construction product in accordance with the applicable harmonized technical specification, as specified by the manufacturer:

Cement-based screed materials, not intended for wear surfaces, for internal use in buildings

4. Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):

Société BOSTIK, le Jade Building — 253 Av du président Wilson — F-93211 La Plaine Saint-Denis Cedex  
[www.bostik.fr](http://www.bostik.fr)

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):

Not applicable

6. System or systems of Assessment and Verification of Constancy of Performance of the construction product in accordance with Annex V:

Level 3

7. In the case of a declaration of performance for a construction product covered by a harmonized standard:

The notified CSTB laboratory No. 0679 determined the product-type on the basis of type tests according to system 3 and issued the test report

8. In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:

Not applicable



# Declaration of Performance

## 9. Declared performance:

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	A1	EN 13813:2002
Emission of corrosive substances or corrosivity of <b>screed materials</b>	see SDS	
Water permeability	NPD	
Water vapor permeability	NPD	
<b>Mechanical strength</b>		
- Compressive strength	≥ C 16	
- Bending strength	≥ F 4	
- Wear resistance (for wear surfaces)	NPD	
Sound insulation		
- Sound absorption	NPD	
Thermal resistance	NPD	
<b>Chemical resistance</b>	NPD	

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and position of company representative

Place and Date

/signature/

/stamp/

Christian  
KLOPFENSTEIN  
Deputy Director-General