



Declaration of Performance

No.: 45-490-300-
01

1. Unique identification code of the product-type:

Adhesives for thermoplastic pipe systems in PVC-U without and with pressure.

2. Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):

SANIPLAS PA. See on the packaging: date of manufacture, batch number, manufacturing center

3. Use or intended uses of the construction product in accordance with the applicable harmonized technical specification, as specified by the manufacturer:

Intended uses: in installations for the transport/discharge/storage of water not intended for human consumption

4. Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):

Société Bostik, Immeuble le Jade — 253 Av du président Wilson — F-93211 La Plaine Saint-Denis Cedex
www.bostik.fr

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):

Not applicable

6. System or systems of Assessment and. Verification of Constancy of Performance of the construction product in accordance with Annex V:

Level 4

7. In the case of a declaration of performance for a construction product covered by a harmonized standard:

The manufacturer has determined the product-type on the basis of type tests and factory production control according to system 4.

8. In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:

Not applicable



Declaration of Performance

9. Declared performance:

Adhesives for thermoplastic pipe systems without pressure:

Essential characteristics	Levels and/or classes	Harmonized technical specifications
Release of hazardous substances	See SDS	EN 14680:2006
- Tearing strength	≥ 3.0 MPa (N/mm ²) at 480 hrs	
- Waterproofing	Satisfactory	
- High temperature resistance	Satisfactory	

Adhesives for thermoplastic pipe systems with pressure:

Essential characteristics	Levels and/or classes	Harmonized technical specifications
Release of hazardous substances	See SDS	EN 14814:2007
- Internal pressure (pressure resistance)	≥ 1,000 hrs	
Tearing strength (Shear strength)	Satisfactory	
Waterproofing (pressure resistance)	≥ 1,000 hrs	
- High temperature resistance (pressure resistance)	Satisfactory	

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name and position of company representative

Place and Date

7/6/13 /signature /stamp/