



# STYLE BASE

## TECHNICAL DATASHEET

Version: 2019-04-02

### PRODUCT DESCRIPTION

Bostik STYLE BASE is a foundation of concrete flooring before applying liquid putty with Bostik STYLE FLOOR. The foundation gives better adhesion and prevents moisture penetration before the application of liquid putty.

### AREA OF USAGE

Bostik STYLE BASE should be used only on concrete floors and indoors in dry areas.

### WORKING INSTRUCTION

The concrete substrate must be clean and maintain good surface strength. Laitance should be mechanically removed. The floor should hold at least + 10C and RF (relative humidity) below 90% and decreasing. Raising damp should not occur. Bostik STYLE BASE should be applied in two layers. The product is ready for use and should not be diluted. After the first treatment has dried (approx. 30 min. at + 20C), apply the second layer 90 degrees offset to the first. Allow to dry (approx. 60 minutes. at + 20C) before applying liquid putty. The liquid putty with Bostik STYLE FLOOR should be applied within 24 hours, otherwise a new foundation must be carried out.


### SAFETY

The product's contents are not classed as hazardous to health or flammable according to applicable legislation. For additional information, please refer to the product's safety data sheet.

### CONTACT US

**TEL +46 (0)42-19 50 00**

**info.se@bostik.com**



## TECHNICAL DATA

Properties before application	
Processing Temp	+ 15C- + 20C, Room and Substrate Temp. Minimal film formation. +10C&period at 40-75 % RF.
Application	Soft brush or Anza Elit roller.
Usage	approx. 0,3 kg/kvm with 2 applications.
Packaging	12 kg can, 50 pounds/pallet
Drying time	30-60 minutes
Cleaning of tools	Water, uncured material.
Storage	Protect from freezing. 12 months. in unopened packaging.

## CONTACT US

**TEL +46 (0)42-19 50 00**

**info.se@bostik.com**

