



# STYLE PROTECT PRIMER

## TECHNICAL DATASHEET

Version: 2019-03-08

### PRODUCT DESCRIPTION

Bostik STYLE PROTECT PRIMER is a water-based primer to impregnate the stained, treated with filler Bostik STYLE FLOOR .

### AREA OF USAGE

Bostik STYLE PROTECT PRIMER is used only indoors and on Bostik STYLE FLOOR to increase adhesion with subsequent treatment of Bostik STYLE PROTECT.

### WORKING INSTRUCTION

Impregnation shall be applied with lint-free roles (type ANZA Elite). Distribute the material evenly over the flap. Allow the compound to dry for approx. 60 minutes. at + 20C) prior to final treatment with STYLE PROTEC.


### SAFETY

According to current applicable legislation, the product's contents are not classified as a health or fire hazard. For additional information, please refer to the product's safety data sheet.

### CONTACT US

**TEL +46 (0)42-19 50 00**

**info.se@bostik.com**



## TECHNICAL DATA

Properties before application	
Processing Temp.	+ 15C - + 25C.
Drying time	1-2 minutes
Consumption	60-80 ml / mq.
application	Anza Elite Roller (does not release lint).
storage	Protect from frost. 12 months storage
Packaging	5 lit. can, 60 pounds / pallet.

## CONTACT US

**TEL +46 (0)42-19 50 00**

**info.se@bostik.com**

