



Bostik

BOSCOSIL MASTIC

NON SKINNING SEALANT

KEY FEATURES

- Permanently non-skinning. Provide a lasting seal
- Moisture resistance. Excellent barrier to moisture vapor
- Excellent adhesion. Adheres well to most substrates
- Microbe resistance.
- Ready to use
- Non sag
- Microbial attack

DESCRIPTION

Bostik Boscosil Mastic is a one-component, non-drying polybutene rubber based mastic that does not harden but rather remains permanently soft and paste-like excellent resistance to water vapour transmission.

RECOMMENDED USES

It is suitable for all kinds of plastics, metals, glass, masonry, and timber. It can also be used in the installation of cool rooms, prefabricated construction, and gasket sealed windscreen to prevent water penetration.

SURFACE PREPARATION

Always ensure that the surface to be sealed are clean, dry and free from oil, dirt and grease.

APPLICATION INSTRUCTION

- Cut nozzle to desired size.
- Insert cartridge to caulking gun.
- Push sealant ahead for uniform bead.
- Clean off excess sealant with kerosene or mineral spirits.

LIMITATION

- It should not be applied in exposed joint where dirt pick-up and hand contact.
- NOT suitable for use in areas subject to considerable dynamic stress.
- NOT for sealing lap joints in mobile homes, truck bodies, etc, which has significant vibration and flexing.

PERFORMANCE PROPERTIES

Colour	White
Specific Gravity (20oC)	1.40± 0.01
Sag or Slump	Non sag paste
Service Temperature	-40oC to +80oC
Application Temperature	-10oC to +40oC

PACKAGING

450g per cartridge

SHELF LIFE AND STORAGE

12 months from date of manufacture in original unopened sausage if store in cool, dry place within the temperature range +5oC to +25oC, 50% relative humidity and out of direct sunlight.

HEALTH AND SAFETY

Bostik Boscosil Mastic contains liquid hydrocarbon solvent. Use in a well ventilated area. When solvents are used, proper precautions must be observed. If contact with skin occurs, wash with soap and water. Avoid contact with eyes. If in eye, hold eye open flood with water for 15 minutes. Seek medical attention. If swallowed, do not induce vomiting, drink water.

LIMITED WARRANTY

The information and recommendations relating to the application and end-use of the product are given in good faith and based on tests which we believe to be reliable. However, no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship, whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. No guarantee of their accuracy can be made because of the great range of field conditions and variation encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with limited warranty only, and on condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik be liable to anyone except for replacement of the products or refund of the purchase price.

PT BOSTIK INDONESIA

Atrium Setiabudi Building, 2nd floor, Suite 203 A
Jl. HR. Rasuna Said Kav. 62 Kuningan
Jakarta 12920, Indonesia
Phone : +62 21 521 0404
Fax : + 62 21 521 0554

www.bostik.com
an ARKEMA company

BOSTIK HOTLINE

Layanan Bantuan +62 21 521 0404

