



# Bostik

## QUELYD SUPER EXPRESS

### WALLPAPER ADHESIVES

#### DESCRIPTION

QUELYD SE is a light weight vinyl wallpaper adhesives that can be used for all types of wallpaper with benefits : excellent bond strength, easy to mix with water, and contains antifungal and biocide additives to prevent mould growth.

#### USES

- Thick, light and heavy weight normal wallpaper
- Washables
- Simplex or Duplex embossed wallpaper
- Paintable wallpapers or woodchip
- Light weight vinyl wallcoverings

#### FEATURES

- Excellent bond strength
- Easy Slide for perfect strip adjustment and pattern matching
- Contains antifungal and biocide additives to prevent mould growth
- Easy to mix with water

#### TYPICAL PROPERTIES

<b>Adhesive type</b>	modified starch-based adhesive in flakes
<b>Colour</b>	Translucent
<b>Paste preparation time</b>	2 minutes
<b>Resistance to micro-organisms</b>	very good, mould resistant formula
<b>Full cure</b>	after 24-48 hours subject to ambient conditions, relative humidity and type of substrate
<b>Yield per pack</b>	6-9 rolls
<b>Working temperature</b>	Between +10° and +25°C

#### APPLICATION INSTRUCTIONS

##### Preparation

Preparation should be in accordance with building standards. Walls must be sound, even, smooth, permanently dry, and free from dust, grease or other contaminants, and have normal porosity.

##### Painted surfaces

Scrape off any flaking paint and smooth the surface with a sanding block. Glossy and semi-gloss paint as well as enameled surfaces should be sanded to bring porosity to the substrate. Eliminate sanding dust. Rinse thoroughly.

##### Old wallpapers and wallcoverings

Remove old wallpaper and colour wash using DISSOUCOL Wallpaper Remover. Rinse thoroughly to get substrate perfectly clean.

To better clean the walls rinse them with bleach and water solution.

Highly porous substrates should be primed with diluted wallpaper paste (SUPER EXPRESS).



#### ADHESIVE PREPARATION

Pour the required quantity of clean water into the bucket depending on the type of wallpaper.

Wallcovering type	Cold water mix (litres)	Number of rolls	Coverage (sq.meters)
Primer	11		70 - 90
Light weight wallpapers	8	8 - 9	40 - 45
Normal weight and heavy weight wallpapers, washables, Simplex or Duplex embossed wallpaper, paintable wallpapers or woodchip	7	7 - 8	35 - 40
Light weight vinyl wallcoverings	6	6 - 7	30 - 35

Stir the water rapidly with a stick. Sprinkle the contents of one packet into water, mixing briskly for approximately 30 seconds. Leave for 2 minutes and stir thoroughly again. The adhesive is ready.

#### PASTING WALLPAPER

Carefully measure the height of the wall, and add 5cm top and bottom for final trimming. Apply the adhesive generously in a regular manner on the back of the wallpaper from center to the edges. Apply plenty to the edges. Fold the strip (or "book") pasted side to pasted side, i.e. bring both edges toward the middle. Make sure that the edges are lined up to avoid early drying of the adhesive. Curling wallcoverings must be rolled up in order to flatten them.

Observe a booking time of 5 to 10 minutes depending on the thickness of the wallpaper and the manufacturer's instructions. Always observe the same booking time throughout hanging operation.

## HANGING WALLPAPER

Use a plumb line to make sure the first strip is perfectly straight. Hang the first strip. Gently slide the paper until the outer edge is lined up with the starting line. Hang subsequent strips edge to edge or according to the manufacturer's recommendations and in the predefined order.

Using a wallpaper brush, carefully press the wallpaper from the top downwards and from the centre toward the edges, taking care to roll out air bubbles and spread out any uneven patches of paste.

Flatten the joints according to manufacturer's instructions. Excess lengths near the ceiling and skirting board will be trimmed using a cutting blade, guided by a broad knife. Immediately wipe off accidental splashes with a clean damp sponge.

## REMARKS

- Carefully read the hanging instructions and strictly follow the manufacturer's recommendations
- Do not start hanging wallcoverings from an outside corner
- Not suitable for use with a pasting machine

## CLEAN-UP

Tools can be easily cleaned with warm water.

## CONSUMPTION

1 pack per 6–9 rolls

## STORAGE

Unlimited if stored in the original unopened pack in dry conditions. Ready mixture can be stored for over a week in a closed container in a frost-free place.

## PACKAGING

250 litre plastic pouch.

## SAFETY

IMPORTANT: before embarking on any work involving QUELYD SUPER EXPRESS the separate Product Safety Data Sheet must be studied carefully by those carrying out the work. Observe good hygiene in use. It is advisable to keep out of reach of children and animals. Use good occupational health and safety practices to avoid contact with eyes and skin. Keep out of reach of children and animals.

Disclaimer : Recommendations for implementation are defined through commonly used standards which should imperatively be respected (or followed). However, in case of first use or special characteristics related to the material support, the site or the environment, prior tests are advised (or are not exempted).

It is recommended to follow our precautionary measures listed in the specification sheets.

## PT BOSTIK INDONESIA

Atrium Setiabudi Building, 2nd floor, Suite 203 A  
Jl. HR. Rasuna Said Kav. 62 Kuningan  
Jakarta 12920, Indonesia  
Phone : +62 21 521 0404  
Fax : + 62 21 521 0554

**www.bostik.com**  
an ARKEMA company

## BOSTIK HOTLINE

Layanan Bantuan +62 21 521 0404

