



Primer SX Black

BLACK WOOD PRIMER

ADVANTAGES

- Improves adhesive bonding
- UV- and water-resistant
- KOMO tested

PRODUCT

Primer SX Black is a black-coloured liquid primer for improving adhesion.

APPLICATIONS

Pre-treatment of smooth-planed wooden support structures to which cladding panels will be bonded.

FEATURES

- Essential for obtaining long-lasting adhesion of cladding panel adhesives (Paneltack and Paneltack HM) on wooden support battens.
- Tested by SHR in accordance with BRL 4101 part 7 and included in the KOMO certificates.
- Colour black, creating a black shadow effect in the joint between the panels.
- UV- and water-resistant.
- Good coverage.

CONSUMPTION

Approximately 3 litres of Primer SX Black required per 100 m² of cladding panel.

METHOD OF USE

Substrate: The substrates must be clean, firm, dry and dust- and grease-free. Moisture content of wood may not exceed 18%.

Preparation: Shake well before use. Keep packaging closed tightly until the product will be used. Do not apply primer straight from the packaging. Pour as much primer as you will use in 30 minutes into a clean, dry paint roller tray. Do not use any residual primer. Close primer tin again immediately. The best adhesion is achieved when the bonding is performed within 6 hours after the primer has dried. Therefore, do not apply primer to areas than cannot be bonded within 6 hours. Avoid touching the cleaned pre-treated surfaces, as this may adversely affect the adhesion. Condensation can also have a negative impact on adhesion. Application of the primer and subsequent sealing or bonding in very humid conditions, such as dense fog, is not recommended.



Application: The primer should be applied with the Bostik Application Set and a clean short-nap velvet-brush roller or suitable clean brush. Apply primer to the bonding surfaces such that the primer forms a continuous coat or film. Apply the primer in a single sufficiently thick layer.

Application temperature: +5 to +30 °C.

Drying time: Minimum drying time 60 minutes.

STORAGE AND STABILITY

Store cool (between +5 and +30°C) and dry. Shelf life of 9 months after production in unopened packaging. Has a limited shelf life once packaging has been opened.

FURTHER INFORMATION

Material safety data sheet is available on bostikdsd.thewerco.com.

Technical data	
Dry content	approx. 65%
Density	1.03 g/ml
Flash point	< 21°C
Drying time	60 minutes (at 20 °C/RH 50%)
Article code	30023350
EAN code	8713572600203
Colour	black
Packaging	1L tin
Packed per	6

Bostik BV / Bostik Benelux BV
Denariusstraat 11
4903 RC Oosterhout
The Netherlands
www.bostik.nl

BOSTIK HOTLINE

Smart help
+31 (0)162 491 000
+32 (0)9 255 1717



Bostik Belux SA - NV
Antwerpse Steenweg 19
9080, Lochristi
Belgium
www.bostik.be