



Primer Q

PU PRIMER

BENEFITS

- Improves the adhesion bond
- Solvent free
- For porous substrates

PRODUCT

Primer Q is a liquid polyurethane based primer for the improvement of the adhesion on specific porous substrates.

APPLICATIONS

Essential to obtain an optimal adhesion on specific substrates such as EQUITONE [tectiva].

PROPERTIES

- Solvent free
- Drying time at least 2 hours.

METHOD OF USE

Substrate: The substrates should have a firm and solid structure and must be clean, dry and dust- and grease free.

Preparation: Keep the packaging well closed until the moment of use. Do not use primers straight from the original packing. Pour as much primer in a clean glass, tin or paint tray, as can be used within 30 minutes. Do not use any left primer residues. Immediately close the original tin. Avoid contact of the cleaned and primed surfaces, because greasy fingers will be of a negative influence on the adhesion. Also condensation can negatively be of influence on the adhesion. It is not recommendable to apply the primer during very high air humidity, for example during dense fog, rain, precipitation in general.

Application: Apply the primer always with a clean brush or clean velvet brush roller. Apply primer on the adhesion surfaces in a closed coat. The primer coat is visible. If this is unacceptable a masking tape can be used to cover the surface parts, where no primer is required.

Application temperature: From +5°C till +30°C.

Drying time: Minimal drying time 120 minutes.

Usage: Depending on the porosity of the surface between 2 - 4 m² per litre.

STORAGE

Store cool (between +5°C and +30°C), dry and frost-free in unopened original packaging. Can be stored for 9 months in unopened bottle, opened packaging has limited shelf life.



FURTHER INFORMATION:

Safety data sheet is available on bostikds.thewerco.com.

Technical data	
Basis	polyurethane
Specific density	approx. 1.2 g/ml
Drying time	120 min. (at +20°C/RH 50%)
Article number	30612664
EAN code	8713572041297
Colour	transparent/brownish
Packaging	1 L tin
Packed per	6

Bostik BV
De Voerman 8
5215 MH 's-Hertogenbosch
T: + 31 (0)73 6244244
infoNL@bostik.com
www.bostik.nl

BOSTIK HOTLINE

Smart help + 31 (0) 73 6 244 244
+ 32 (0) 9 255 17 17



Bostik Belux SA - NV
Meulestedekaai 86
B-9000 Gent
T: + 32 (0) 92551717
info@bostik.be
www.bostik.be