

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020Revision Date: 08-Oct-2020
Revision Number 1**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier****Product Name** BOSTIK QUICK DRYING FLEXACRYL GREY
Pure substance/mixture Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Primers, Sealers, and Undercoaters.
Uses advised against None known.**1.3. Details of the supplier of the safety data sheet****Company Name**Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****Emergency Telephone** No information available**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Skin sensitisation Category 1 - (H317)**2.2. Label Elements**

Contains: 2-methyl-2H-isothiazol-3-one [MIT], 1,2-benzisothiazol-3(2H)-one [BIT], reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]

**Signal word**
WARNING**Hazard statements**
H317 - May cause an allergic skin reaction.**EU Specific Hazard Statements**

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P261 - Avoid breathing vapours.

P280 - Wear protective gloves and eye/face protection.

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap.

P501 - Dispose of contents/ container to an approved waste disposal plant.

2.3. Other Hazards

No information available

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

| Chemical name | EC No | CAS No | Weight-% | Classification according to Regulation (EC) No. 1272/2008 [CLP] | Specific concentration limit (SCL) | REACH Registration Number |
|------------------------------------|-----------|------------|----------------|---|------------------------------------|---------------------------|
| Titanium dioxide | 236-675-5 | 13463-67-7 | 10 - <20 | Carc. 2 (H351i) | | 01-2119489379-17-XXXX |
| 1,2-benzisothiazol-3(2H)-one [BIT] | 220-120-9 | 2634-33-5 | 0.01 - <0.05 | Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411) (M Factor Acute =1) | Skin Sens. 1 :: C>=0.05% | 01-2120761540-60-XXXX |
| 2-methyl-2H-isothiazol-3-one [MIT] | 220-239-6 | 2682-20-4 | 0.0015 - <0.01 | Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Aquatic Acute 1 | Skin Sens. 1 :: C>=0.0015% | 01-2120764690-50-xxxx |

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

| | | | | | | |
|--|-----------|------------|---------|--|--|---------------------------|
| | | | | (H400) Aquatic Chronic 1 (H410) (M Factor Acute =10) | | |
| reaction mass of 5-chloro-2-methyl-2H-iso thiazol-3-one and 2-methyl-2H-isothiazol-3 -one (3:1) [C(M)IT/MIT] | 611-341-5 | 55965-84-9 | <0.0015 | Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute = 100 M Factor Chronic = 100 | Eye Dam. 1 :: C>=0.6% Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015% | 01-2120764691- 48-XXXX |

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|-----------------------|---|
| General advice | Show this safety data sheet to the doctor in attendance. |
| Inhalation | Remove to fresh air. IF exposed or concerned: Get medical advice/attention. |
| Eye contact | Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor. |
| Skin contact | Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. |
| Ingestion | Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. |

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supercedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

5.1. Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon dioxide (CO₂). Silicon oxides.

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Other information Ventilate the area. Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

7.3. Specific end use(s)

Specific Use(s)
Primers, Sealers, and Undercoaters.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Derived No Effect Level (DNEL) No information available

| Derived No Effect Level (DNEL) | | | |
|---|----------------|--------------------------------|---------------|
| Titanium dioxide (13463-67-7) | | | |
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| worker Long term Local health effects | Inhalation | 10 mg/m ³ | |

| 1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5) | | | |
|---|----------------|--------------------------------|---------------|
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| worker Long term Systemic health effects | Inhalation | 6.81 mg/m ³ | |
| worker Long term Systemic health effects | Dermal | 0.966 mg/kg bw/d | |

| Derived No Effect Level (DNEL) | | | |
|--|----------------|--------------------------------|---------------|
| Titanium dioxide (13463-67-7) | | | |
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| Consumer Long term Systemic health effects | Oral | 700 mg/kg bw/d | |

| 1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5) | | | |
|---|----------------|--------------------------------|---------------|
| Type | Exposure route | Derived No Effect Level (DNEL) | Safety factor |
| Consumer Long term Systemic health effects | Inhalation | 1.2 mg/m ³ | |
| Consumer Long term | Dermal | 0.345 mg/kg bw/d | |

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

| | | | |
|-------------------------|--|--|--|
| Systemic health effects | | | |
|-------------------------|--|--|--|

Predicted No Effect Concentration (PNEC) No information available.
(PNEC)

| Predicted No Effect Concentration (PNEC) | |
|--|--|
| Titanium dioxide (13463-67-7) | |
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Marine water | 0.0184 mg/l |
| Freshwater sediment | 1000 mg/kg |
| Freshwater | 0.184 mg/l |
| Marine sediment | 100 mg/kg |
| Soil | 100 mg/kg |
| Microorganisms in sewage treatment | 100 mg/l |
| Freshwater - intermittent | 0.193 mg/l |

| 1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5) | |
|--|--|
| Environmental compartment | Predicted No Effect Concentration (PNEC) |
| Freshwater | 4.03 µg/l |
| Marine water | 0.403 µg/l |
| Sewage treatment plant | 1.03 mg/l |
| Freshwater sediment | 49.9 µg/l |
| Marine sediment | 4.99 µg/l |
| Soil | 3 mg/kg dry weight |

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Avoid contact with eyes.
Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Skin and body protection Wear protective gloves and protective clothing. Avoid contact with skin, eyes or clothing.
Respiratory protection During spraying wear suitable respiratory equipment.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Colour Grey
Odour Sweet
Odour threshold No information available

| Property | Values | Remarks • Method |
|--|----------------------------|------------------|
| pH | No data available | |
| pH (as aqueous solution) | 7 - 8.5 | |
| Melting point / freezing point | No data available | |
| Boiling point / boiling range | 100 °C | |
| Flash point | > 80 °C | |
| Evaporation rate | No data available | |
| Flammability (solid, gas) | Not applicable for liquids | |
| Flammability Limit in Air | | |
| Upper flammability or explosive limits | No data available | |
| Lower flammability or explosive | No data available | |

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

limits

| | |
|---------------------------|-------------------|
| Vapour pressure | No data available |
| Vapour density | No data available |
| Relative density | No data available |
| Water solubility | Miscible in water |
| Solubility(ies) | No data available |
| Partition coefficient | No data available |
| Autoignition temperature | No data available |
| Decomposition temperature | No data available |
| Kinematic viscosity | No data available |
| Dynamic viscosity | 525000 mPa s |
| Explosive properties | No data available |
| Oxidising properties | No data available |

9.2. Other information

| | |
|-------------------|--------------------------|
| Solid content (%) | No information available |
| VOC Content (%) | 30 g/L |
| Density | 1.16 |

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO₂). Hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information .

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

| | |
|---------------------|---|
| Inhalation | Based on available data, the classification criteria are not met. |
| Eye contact | Based on available data, the classification criteria are not met. |
| Skin contact | May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). |
| Ingestion | Based on available data, the classification criteria are not met. |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|--------------------------|---|-------------------------|
| Titanium dioxide 13463-67-7 | >10000 mg/kg (Rattus) | LD50 > 10000 mg/Kg | >5 mg/l |
| 1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5 | =670 mg/kg (Rattus) | LD50 > 2000 mg/kg (Rattus) | |
| 2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4 | LD50 =285 mg/Kg (Rattus) | LD50 >242 mg/Kg (Rattus) | =0.11 mg/L (Rattus) 4 h |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9 | =53 mg/kg (Rattus) | LD50 = 87.12 mg/kg (Oryctolagus cuniculus) | |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

| Component Information | | | |
|--|------------|----------------|-------------|
| Titanium dioxide (13463-67-7) | | | |
| 2-methyl-2H-isothiazol-3-one [MIT] (2682-20-4) | | | |
| Method | Species | Exposure route | Results |
| OECD Test No. 406: Skin Sensitisation | Guinea pig | Dermal | Sensitizing |

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

| Chemical name | European Union |
|--------------------------------|----------------|
| Titanium dioxide 13463-67-7 | Carc. 2 |

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

| Chemical name | Algae/aquatic plants | Fish | Toxicity to microorganisms | Crustacea | M-Factor | M-Factor (long-term) |
|--|---|--|----------------------------|--|----------|----------------------|
| Titanium dioxide 13463-67-7 | LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203 | - | - | - | | |
| 1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5 | EC50 3Hr 13mg/l (activated sludge) (OECD 209) | LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006 | - | EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202 | 1 | 1 |
| 2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4 | EC50 (72hr) 0.157 mg/l (Pseudokirchneriella subcapitata) (OECD 201) | EC50 (96hr) 5.71 mg/l (Oncorhynchus mykiss) OECD 203 | - | EC50 (48hr) 1.68 mg/l (Daphnia) (OECD 202) | 10 | 1 |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9 | EC50 (72h) =0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201) | EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211) | - | EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202) | 100 | 100 |

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information

2-methyl-2H-isothiazol-3-one [MIT] (2682-20-4)

| Method | Exposure time | Value | Results |
|---|---------------|-----------|---------------|
| OECD Test No. 308: Aerobic and Anaerobic Transformation in Aquatic Sediment Systems | | Half-life | 1.28-2.1 days |

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

| | | | |
|---|--|--------------------------|--------------------------------|
| OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test | | biodegradation Half-life | Readily biodegradable 4.1 days |
|---|--|--------------------------|--------------------------------|

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

| Chemical name | Partition coefficient | Bioconcentration factor (BCF) |
|---|-----------------------|-------------------------------|
| 1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5 | 0.7 | 6.95 |
| 2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4 | -0.32 | 3.16 |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9 | - | 3.16 |

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB. .

| Chemical name | PBT and vPvB assessment |
|---|--|
| Titanium dioxide 13463-67-7 | The substance is not PBT / vPvB PBT assessment does not apply |
| 1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5 | The substance is not PBT / vPvB |
| 2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4 | The substance is not PBT / vPvB |
| reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9 | The substance is not PBT / vPvB |

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|---------------------------------|----------------|
| 14.1 UN number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing group | Not regulated |
| 14.5 Environmental hazards | Not applicable |
| 14.6 Special Provisions | None |

IMDG

| | |
|---|----------------|
| 14.1 UN number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing group | Not regulated |
| 14.5 Marine pollutant | Np |
| 14.6 Special Provisions | None |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable |

Air transport (ICAO-TI / IATA-DGR)

| | |
|---------------------------------|----------------|
| 14.1 UN number | Not regulated |
| 14.2 Proper Shipping Name | Not regulated |
| 14.3 Transport hazard class(es) | Not regulated |
| 14.4 Packing group | Not regulated |
| 14.5 Environmental hazards | Not applicable |
| 14.6 Special Provisions | None |

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

| Chemical name | French RG number |
|---|------------------|
| 1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5 | RG 65 |

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed
H302 - Harmful if swallowed
H310 - Fatal in contact with skin
H311 - Toxic in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H330 - Fatal if inhaled
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H411 - Toxic to aquatic life with long lasting effects

Legend

| | |
|---------|--|
| TWA | TWA (time-weighted average) |
| STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Ceiling Limit Value |
| * | Skin designation |
| SVHC | Substance(s) of Very High Concern |
| PBT | Persistent, Bioaccumulative, and Toxic (PBT) Chemicals |

SAFETY DATA SHEET

BOSTIK QUICK DRYING FLEXACRYL GREY
Supersedes Date: 08-Oct-2020

Revision Date: 08-Oct-2020
Revision Number 1

| | |
|---------|---|
| vPvB | Very Persistent and very Bioaccumulative (vPvB) Chemicals |
| STOT RE | Specific target organ toxicity - Repeated exposure |
| STOT SE | Specific target organ toxicity - Single exposure |
| EWC | European Waste Catalogue |

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date: 08-Oct-2020

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet