

CEMENTONE WATERSEAL
 Supersedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1. Product Identifier

Product Name CEMENTONE WATERSEAL
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Primers, Sealers, and Undercoaters.
Uses advised against None known.

1.3. Details of the supplier of the safety data sheet
Company Name

Bostik Limited
 Common Rd
 ST16 3EH
 Stafford UK
 Tel: +44 (1785) 27 26 25
 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification
2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity — repeated exposure	Category 1 - (H372)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 3 - (H226)

2.2. Label Elements

Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Petroleum distillates, hydrotreated light



Signal word
 DANGER

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

Hazard statements

H304 - May be fatal if swallowed and enters airways.
H336 - May cause drowsiness or dizziness.
H372 - Causes damage to organs through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.
H226 - Flammable liquid and vapour.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 - Do not breathe mist/vapours/spray.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves and eye/face protection.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P391 - Collect spillage.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P501 - Dispose of contents/ container to an approved waste disposal plant.

Additional information

This product requires tactile warnings if supplied to the general public. This product requires child resistant fastenings if supplied to the general public.

2.3. Other Hazards

No information available

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	919-446-0	RR-91855-8	80 - 100	STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 3 (H226) (EUH066)		01-2119458049-33-XXXX
Petroleum distillates, hydrotreated light	265-149-8	64742-47-8	1 - <5	Asp. Tox. 1 (H304) (EUH066)		01-2119484819-18-XXXX

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supercedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.
Self-protection of the first aider	Remove all sources of ignition. See section 8 for more information. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.
------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
---	---

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supercedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions See section 8 for more information. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapours or mists. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Store away from other materials.

7.3. Specific end use(s)

Specific Use(s)

Primers, Sealers, and Undercoaters.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	330 mg/m ³	
worker Long term Systemic health effects	Dermal	44 mg/kg bw/d	

Petroleum distillates, hydrotreated light (64742-47-8)

Derived No Effect Level (DNEL)			
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (RR-91855-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	71 mg/m ³	
Consumer Long term Systemic health effects	Dermal	26 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	26 mg/kg bw/d	

Petroleum distillates, hydrotreated light (64742-47-8)			
Type	Exposure route	Derived No Effect Level	Safety factor

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

		(DNEL)	
Consumer Long term Systemic health effects	Oral	19 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Eye protection must conform to standard EN 166.
Hand protection Wear protective gloves. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection Gloves made of plastic or rubber. Antistatic footwear. Wear fire/flame resistant/retardant clothing.

Environmental exposure controls Local authorities should be advised if significant spillages cannot be contained. Do not allow into any sewer, on the ground or into any body of water. Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Colour No information available
Odour Characteristic
Odour threshold No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	151 °C	
Flash point	38 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supercedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	No information available
Density	No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Skin contact Repeated exposure may cause skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	LD50 >15000 mg/Kg (Rattus) OECD 401	LD50 > 3400 mg/kg (Rattus) OECD 402	LC50 (4hrs) >13.1 mg/l (Rattus)
Petroleum distillates, hydrotreated light 64742-47-8	>5000 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	>5.2 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics	EL50 (72h) = 4.1 mg/l (Pseudokirchner)	10-30 mg/l	-	10-30mg/l (daphnia magna)		

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

(2-25%) RR-91855-8	ella subcapitata) OECD 401					
Petroleum distillates, hydrotreated light 64742-47-8	-	LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss) LC50: =45mg/L (96h, Pimephales promelas)	-	LC50: =4720mg/L (96h, Den-dronereide s heteropoda)		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Petroleum distillates, hydrotreated light 64742-47-8	-	159

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB. .

Chemical name	PBT and vPvB assessment
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) RR-91855-8	The substance is not PBT / vPvB
Petroleum distillates, hydrotreated light 64742-47-8	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supersedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number	UN1263
14.2 Proper Shipping Name	Paint related material, Environmentally Hazardous
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing group	III
Description	UN1263, Paint related material, 3, III, (D/E), Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special Provisions	163, 650, 367
Classification code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	30

IMDG

14.1 UN number	UN1263
14.2 Proper Shipping Name	Paint related material (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), Marine Pollutant
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1263, Paint related material (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), 3, III, (38°C c.c.), Marine Pollutant
14.5 Marine pollutant	P.
14.6 Special Provisions	163, 223, 367, 955
Limited Quantity (LQ)	5 L
EmS-No	F-E, S-E
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number	UN1263
14.2 Proper Shipping Name	Paint related material
14.3 Transport hazard class(es)	3
14.4 Packing group	III
Description	UN1263, Paint related material, 3, III
14.5 Environmental hazards	Yes
14.6 Special Provisions	A3, A72, A192
Limited Quantity (LQ)	10 L
ERG Code	3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No.

SAFETY DATA SHEET

CEMENTONE WATERSEAL
Supercedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020
Revision Number 1

1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Petroleum distillates, hydrotreated light 64742-47-8	RG 84

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R10), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 3

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

SAFETY DATA SHEET

CEMENTONE WATERSEAL

Supersedes Date: 25-Sep-2020

Revision Date: 25-Sep-2020

Revision Number 1

EUH066 - Repeated exposure may cause skin dryness or cracking
H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H336 - May cause drowsiness or dizziness
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision Date: 25-Sep-2020

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet