

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Product name : BoscoSeal PU-X
Product code : 50-2-5-BoscoSeal-PU-X

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Industrial/Professional use spec : For professional use only
Industrial
Use of the substance/mixture : One component water proofing and protection elastomeric material, based on polyurethane resin for the building industry

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Bostik Hellas S.A.
3, Metsovou Str, Moschato
P.O. Box 183 46
Piraeus, Athens - Greece
T +30 210 4831140
info@bostik.com - www.bostik.com/greece

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3 H226
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Repeated exposure, Category 2 H373
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Warning

Hazardous ingredients :

Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H373 - May cause damage to organs through prolonged or repeated exposure.

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P260 - Do not breathe vapours. P280 - Wear protective gloves, face protection, eye protection. P233 - Keep container tightly closed. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271 - Use only outdoors or in a well-ventilated area. P501 - Dispose of contents to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH204 - Contains isocyanates. May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	14 – 15	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Wash with plenty of water/.... Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes damage to organs.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.
Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid breathing spray, fume, vapours.
Hygiene measures : Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources. Keep container tightly closed.
Incompatible products : Strong bases. Strong acids. water, amines and alcohol's.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene (1330-20-7)

EU - Occupational Exposure Limits

IOELV TWA (mg/m ³)	221 mg/m ³
IOELV TWA (ppm)	50 ppm
IOELV STEL (mg/m ³)	442 mg/m ³
IOELV STEL (ppm)	100 ppm

8.2. Exposure controls

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous liquid.
Colour	: Grey. white. Black.
Odour	: characteristic.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 35 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: No data available

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,42 g/cm ³
Solubility	: organic solvents.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: > 20,5 mm ² /s
Viscosity, dynamic	: 4000 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 212 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None under normal use. Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases. water, amines and alcohol's.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene (1330-20-7)

LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	12126 mg/kg
LC50 inhalation rat (Vapours - mg/l/4h)	27124 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

BoscoSeal PU-X

Viscosity, kinematic	> 20,5 mm ² /s
----------------------	---------------------------

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
---	---

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene (1330-20-7)

LC50 fish 1	2,6 – 11,23 mg/l
EC50 Daphnia 1	> 3,4 mg/l

12.2. Persistence and degradability

BoscoSeal PU-X

Persistence and degradability	No available data.
-------------------------------	--------------------

12.3. Bioaccumulative potential

BoscoSeal PU-X

Bioaccumulative potential	No available data.
---------------------------	--------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information	: Avoid release to the environment.
------------------------	-------------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a hazardous or special waste collection point.
--	---

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Additional information : Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : UN 1139
UN-No. (IMDG) : UN 1139
UN-No. (IATA) : UN 1139
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : COATING SOLUTION
Proper Shipping Name (IMDG) : COATING SOLUTION
Proper Shipping Name (IATA) : Coating solution
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable
Transport document description (ADR) : UN 1139 COATING SOLUTION (NOT SUBJECT TO THE PROVISIONS OF ADR
- The product is packed in receptacles of less than 450 litres capacity.
- Exempted according to 2.2.3.1.5 (Viscous substance exemption)), 3, III, (D/E)
Transport document description (IMDG) : UN 1139 COATING SOLUTION (NOT SUBJECT TO THE PROVISIONS OF IMDG CODE FOR THE MARKING, LABELLING AND TESTING OF PACKAGES IN CHAPTERS 4.1, 5.2, AND 6.1.
- The product is packed in receptacles not exceeding 30 L capacity
- The following statement shall be included in the transport document:
"Transport in accordance with 2.3.2.5 of the IMDG Code."
) , 3, III
Transport document description (IATA) : UN 1139 Coating solution (Not restricted per IATA-DGR special provision A3 and ICAO special provision 223), 3, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : III
Packing group (IMDG) : III
Packing group (IATA) : III
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable


14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 640E
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3YE

Transport by sea

Special provisions (IMDG) : 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 212 g/l

15.1.2. National regulations

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene is listed

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

BoscoSeal PU-X

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Classification according to Regulation (EC) No. 1272/2008 [CLP]:	
Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT RE 2	H373

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH204	Contains isocyanates. May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.