



Bosco seal Primer Transparent

ONE COMPONENT PRIMER / ADHESION IMPROVER FOR NON-POROUS
SUBSTRATES

TECHNICAL DATA SHEET

BENEFITS

- Easy and fast application
- Unaffected by weather conditions
- Highly improves adhesion to non-porous substrates

PRODUCT DESCRIPTION

Bostik Bosco seal Primer Transparent is one-component, ready to use, transparent, rapid curing primer/adhesion improver. It is used as a primer before applying Bosco seal PU transparent over non-porous tiles and glass.

APPLICATIONS

- To prime non-porous tiles, glassed tiles, porcelain tiles, glass.

CONSUMPTION

Maximum 0.1lt / m². do not exceed this consumption or/and leave any ponding primer on the surface.

DIRECTIONS OF USE

- Bostik Bosco seal Primer Transparent should be applied with a piece of cloth, as a cleaner over the well cleaned and dry tiles.
- Please clean well the tiles surface to remove any dust, dirt, oil agents and salt residues before applying the primer.
- Apply Bosco seal PU transparent immediately after the primer fully dries (10-15 minutes).



TECHNICAL DATA

Color	Transparent
Curing time (h)	10 – 15 minutes
Specific weight (gr/cm ³)	0.80 – 0.90
Application temperature	Between + 5°C and + 35°C
Flash point	>50°C

Technical data are approximately provided according to a temperature of + 20°C and a relative humidity of 50%.

LIMITATIONS

Do not consume more than 0.1lt/m². After cleaning well tiles with Transparent Primer, do not leave any liquid primer ponding on the surface.

SURFACE PREPARATION

- Clean well the tiles with high pressure washing to remove dirt and dust.
- Use oil detergent (diluted in water) to clean well the tiles from any oily agents (if needed).
- Use anti-calc detergent (diluted in water) to clean well the tiles from any salt residues.
- Wash well the surface with plenty of water to remove detergent residues.
- Leave the surface to dry well. Both tiles and joints should be dry when you apply Transparent Primer.

CLEANING

Wash the cloths used for Bostik Boscoseal Primer Transparent application and allow them to dry well before using again.

COLORS

Transparent

PACKAGING

1lt metal pail

SHELF LIFE

- It should be protected from water and adverse weather conditions.
- It should be kept dry and cool on wooden pallets at between +10°C and +25°C in low moisture conditions.
- Opened products should be re-closed immediately and consumed within 24 hours.
- Shelf life is maximum 12 months conditional to complying with the above-mentioned storage conditions.

HEALTH AND SAFETY

On contact, uncured membrane causes irritation. Gloves and protective goggles must be worn during stirring, application, and use. Avoid contact with skin, eyes and avoid breathing in vapor. If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, do not induce vomiting. Give a glass of water. If skin contact occurs, remove contaminated clothing and wash skin thoroughly for a minimum of 15 minutes and see a doctor.

Please read MSDS (Material Safety Data Sheet) before application.

The present Disclaimer contains general information and suggestions with regard to using in general (including but not limited to adaptation, combination etc.) the products ("the Products") supplied by Bostik Hellas S.A. ("the Company" or "Bostik Hellas") as displayed in the present Technical Data Sheet.

This Technical Data Sheet covers just one of a large range of Products supplied by the Company and is to be carefully read before using any of the Products or part(s) thereof. Use, in part or in whole, of any of the Products constitutes acceptance of the contents hereof.

This Technical Data Sheet supersedes all previous technical data sheets relating to the Products. Please ensure that this is the current version and destroy all previous technical data sheets. If in doubt, contact the Company respectively.

In case of any inconsistency with the terms and directions of use and/or any other disclaimer and/or any other exclusion or limitation of liability of the Company appearing on the Products or the packaging or manuals thereof, the terms of the present Disclaimer shall prevail.

The contents of the present Disclaimer are based on current know how and experience of the Company and the Company undertakes no obligation to update, complete, revise or amend this Disclaimer even in case the information contained herein changes materially or in light of future know-how.

Bostik Hellas has made every possible effort to ensure the validity of information hereby contained, but it shall not by any means be liable for possible inadvertent omission and/or non-completeness of this disclaimer.

Bostik Hellas makes hereby no representations or warranties of any nature whatsoever, oral or written, express or implied, regarding the Products or any other matter, including implied warranties of merchantability, fitness for a particular purpose, non-infringement, suitability, therefore no such requirement shall incur against the Company either on the basis of written information, suggestion or advice provided.

The present does not constitute and may not be considered as any kind of guarantee of the Products and/or their characteristics and/or properties neither forms an agreement on any quality of the Products.

The recommendations contained herein constitute the general context, compliance with which is absolutely connected with the use and application of the Products by the user in accordance with their purpose, including, but not limited to, in terms of keeping and storage under safe and appropriate conditions.

Bostik Hellas, therefore, undertakes no liability with respect to delivery, installation, storage and keeping conditions and it shall not be liable to the Products user or any third persons in relation to any loss for or damage due to misuse; or use which is not in accordance with the instructions for use of the Products in this Technical Data Sheet or on the Products operating manuals or any other instructions issued by the Company and provided to the user at the time of purchase; or improper support of the Products; or interventions or manipulation in the use or application of the Products; or use of other material not supplied by or approved for use by Bostik Hellas; or external causes.

For full information on the Products and/or advice on the use and/or application thereof, contact the Company and its trained personnel and associates. For special technical advice, contact our Technical Services Department.

Bostik Hellas accepts no liability on the purpose of or due to this document.

Buyers and users recognize and accept that the choice of the Products is not related by any means to the present document and they store, use and apply the Products entirely on their own responsibility. This Disclaimer sets out no liability of the Company to such users in respect of any of the Products displayed in this Technical Data Sheet, including any liability for acts or omissions of Bostik Hellas employees, agents, consultants and/or sub-contractors.

The Company shall not be liable to the buyers and users of the Products or any third persons for economic losses, losses of profits or business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as such is not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) arising out of or in connection with the use of any of the Products to which this Technical Data Sheet refers by their users.

Product orders are accepted and governed by Bostik Hellas sales and delivery current terms and conditions as uploaded in the Company's website. This document was last revised on 01/06/2019

Distribution

Bostik Hellas S.A

3, Metsovou Str, Moschato, 183 46, Pireaus, Greece

T: + 30 210 48 31 140, Fax: + 30 210 48 31 125,

E-mail: info@bostik.com | www.bostik.com/greece

BOSTIK HOTLINE

**Technical Support
(+30)801 11 31140**

