

# Foamtape

## SPACER AND FIXATION FOR BONDING CLADDING PANELS

### ADVANTAGES

- High initial strength in variable weather conditions.
- Specially designed for cladding panel bonding

### PRODUCT

Foamtape is a double-sided adhesive foam tape with a release film on one side, specially developed as part of the adhesive system for bonding cladding panels.

### APPLICATIONS

Provides initial adhesion to the cladding panel and guarantees sufficient thickness of the adhesive bead.

### METHOD OF USE

Once the primers have fully dried, Foamtape is applied in continuous strips to the vertical parts of the support structure only. For the correct position and length of the foam tape, please take into account the dimensions of the supporting battens, the panel dimensions and the necessary space for the beads of adhesive. Press Foamtape firmly and cut to length with a sharp knife. Do not remove the protective film immediately after applying Foamtape; wait until the adhesive has been applied (and you are ready to bond the cladding panels). Hereafter the panel must be placed within the prescribed time. Correction is still possible until the panel touches the Foamtape. For proper positioning of the cladding panel, use spacers, support blocks or horizontal supporting laths. For easier handling a glass suction clamp also can be useful. Once the panel is positioned correctly, the panel must be pressed down by gently rubbing over the entire length of the Foamtape. Foamtape may not be compressed. Now it is no longer possible to correct the panel position.

**Application temperature:** +5 to +30 °C.

### STORAGE AND STABILITY

Store frost-free. Can be stored for 24 months (after production date) in unopened packaging in dry conditions at temperatures of +5 to +30 °C.



Technical data	
Thickness	≥ 3 mm
Width	12 mm
Foam	physically crosslinked polyolefin
Density	approx. 60 kg/m <sup>3</sup>
Release film	siliconized paper (with Bostik logo printed on top)
Application temperature	+5 to +30 °C
Shear strength	approx. 0.27 N/mm <sup>2</sup>
Tensile strength	approx. 0.27 N/mm <sup>2</sup>
Article code	30182771
EAN code	8713572030093
Colour	black
Packaging	25 m roll
Packed per	20

#### BOSTIK HOTLINE

Smart help +31 (0)162 491 000  
+32 (0)9 255 1717



**Bostik BV / Bostik Benelux BV**  
Denariusstraat 11  
4903 RC Oosterhout  
The Netherlands  
[www.bostik.nl](http://www.bostik.nl)

**Bostik Belux SA - NV**  
Antwerpse Steenweg 19  
9080, Lochristi  
Belgium  
[www.bostik.be](http://www.bostik.be)