



Boscoseal PU-X-Moderator

CURING AGENT

TECHNICAL DATA SHEET

BENEFITS

- Provides curing acceleration for Boscoseal PU-X or PU-Pro especially during winter (low temperature and humidity)
- Non-toxic
- The coating has improved mechanical properties
- Increase the film's thixotropy
- Improves the hardness
- Improves the chemical resistance of the final membrane
- Ideal for vertical applications
- Give the ability for thick coats with the addition of the curing accelerator in PU-X or PU-Pro
- Eliminates bubbling and surface defects

PRODUCT DESCRIPTION

Bostik Boscoseal PU-X-Moderator is a ready to use, transparent, curing agent especially designed for **Bostik Boscoseal PU-X** and **Bostik Boscoseal PU-Pro**. It is designed in order to achieve the best function between pot-life and cure speed. Not only improves the drying time of the referred Boscoseal range of products but also boosts the mechanical properties, hardness and chemical resistance of the final membrane.

APPLICATIONS

- To improve the drying time.
- To increase mechanical properties, hardness and chemical resistance of the coating.
- To achieve thicker coats than normal.
- For applications on vertical substrates.

DIRECTIONS OF USE

- Shake well the pail before the use of the product.
- Pour the content of the pail into the pail containing Boscoseal PU-X or Boscoseal PU-Pro and mix thoroughly using a low speed electric mixer. After that apply immediately.

LIMITATIONS

Bostik Boscoseal PU-X:

Do not apply in thick coats, at a consumption higher than 1.8kg/m² per coat.

Bostik Boscoseal PU-Pro:

Do not apply in thick coats, at a consumption higher than 1.6kg/m² per coat.

TECHNICAL DATA

Color	Transparent
Appearance	Flammable liquid
Mixing ratio	PU-X/Moderator 25kg/0.50 kg PU-Pro/Moderator 25kg/0.25 kg
Specific weight (gr/cm ³)	0.90-1.00
Pot life	About 30 min at 25°C
Application temperature	Between + 5°C and + 35°C
Resistance of hardened coating	PU-X/Moderator Between -40°C and + 90°C PU-Pro/Moderator Between -40°C and + 60°C

CLEANING

Clean tools and equipment using BOSTIK solvent (for other types of solvent, please consult Bostik Technical Dept.)

COLORS

Transparent

PACKAGING

0.25kg metal pail

SHELF LIFE

- The product must be protected from water, frost and adverse weather conditions.
- It should be kept dry and cool at between +5°C and +25°C in moisture free conditions.
- Opened packaging should be closed immediately after use and consumed within 24 hours.
- Shelf life is 12 months conditional
- Keep out from the reach of children when complying with the above-mentioned storage conditions.

HEALTH AND SAFETY

On contact, uncured membrane causes irritation. Gloves and protective goggles must be worn during stirring, application, and use. Avoid contact with skin, eyes and avoid breathing in vapor. If poisoning occurs, contact a doctor or Poisons Information Centre. If swallowed, do not induce vomiting. Give a glass of water. If skin contact occurs, remove contaminated clothing and wash skin thoroughly for a minimum of 15 minutes and see a doctor.


Please read MSDS (Material Safety Data Sheet) before application.

POT LIFE

The graph below shows the performance of viscosity of Boscoseal PU-X and Boscoseal PU-Pro over time.

Blue line : Bostik Boscoseal PU-X 25kg with 0,5kg of Boscoseal PU-X Moderator

Red line : Bostik Boscoseal PU-Pro 25kg with 0,25kg of Boscoseal PU-X Moderator



The present Disclaimer contains general information and suggestions with regard to using in general (including but not limited to adaptation, combination etc.) the products ("the Products") supplied by Bostik Hellas S.A. ("the Company" or "Bostik Hellas") as displayed in the present Technical Data Sheet.

This Technical Data Sheet covers just one of a large range of Products supplied by the Company and is to be carefully read before using any of the Products or part(s) thereof. Use, in part or in whole, of any of the Products constitutes acceptance of the contents hereof.

This Technical Data Sheet supersedes all previous technical data sheets relating to the Products. Please ensure that this is the current version and destroy all previous technical data sheets. If in doubt, contact the Company respectively.

In case of any inconsistency with the terms and directions of use and/or any other disclaimer and/or any other exclusion or limitation of liability of the Company appearing on the Products or the packaging or manuals thereof, the terms of the present Disclaimer shall prevail.

The contents of the present Disclaimer are based on current know how and experience of the Company and the Company undertakes no obligation to update, complete, revise or amend this Disclaimer even in case the information contained herein changes materially or in light of future know-how.

Bostik Hellas has made every possible effort to ensure the validity of information hereby contained, but it shall not by any means be liable for possible inadvertent omission and/or non-completeness of this disclaimer.

Bostik Hellas makes hereby no representations or warranties of any nature whatsoever, oral or written, express or implied, regarding the Products or any other matter, including implied warranties of merchantability, fitness for a particular purpose, non-infringement, suitability, therefore no such requirement shall incur against the Company either on the basis of written information, suggestion or advice provided.

The present does not constitute and may not be considered as any kind of guarantee of the Products and/or their characteristics and/or properties neither forms an agreement on any quality of the Products.

The recommendations contained herein constitute the general context, compliance with which is absolutely connected with the use and application of the Products by the user in accordance with their purpose, including, but not limited to, in terms of keeping and storage under safe and appropriate conditions.

Bostik Hellas, therefore, undertakes no liability with respect to delivery, installation, storage and keeping conditions and it shall not be liable to the Products user or any third persons in relation to any loss for or damage due to misuse; or use which is not in accordance with the instructions for use of the Products in this Technical Data Sheet or on the Products operating manuals or any other instructions issued by the Company and provided to the user at the time of purchase; or improper support of the Products; or interventions or manipulation in the use or application of the Products; or use of other material not supplied by or approved for use by Bostik Hellas; or external causes.

For full information on the Products and/or advice on the use and/or application thereof, contact the Company and its trained personnel and associates. For special technical advice, contact our Technical Services Department.

Bostik Hellas accepts no liability on the purpose of or due to this document.

Buyers and users recognize and accept that the choice of the Products is not related by any means to the present document and they store, use and apply the Products entirely on their own responsibility. This Disclaimer sets out no liability of the Company to such users in respect of any of the Products displayed in this Technical Data Sheet, including any liability for acts or omissions of Bostik Hellas employees, agents, consultants and/or sub-contractors.

The Company shall not be liable to the buyers and users of the Products or any third persons for economic losses, losses of profits or business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as such is not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) arising out of or in connection with the use of any of the Products to which this Technical Data Sheet refers by their users.

Product orders are accepted and governed by Bostik Hellas sales and delivery current terms and conditions as uploaded in the Company's website. This document was last revised on 01/06/2019

Distribution

Bostik Hellas S.A

3, Metsovou Str, Moschato, 183 46, Pireaus, Greece

T: + 30 210 48 31 140, Fax: + 30 210 48 31 125,

E-mail: info@bostik.com | www.bostik.com/greece

