



ACRYL PEINTURE

ACRYLIC SEALANT MASTIC SPECIAL PAINTER.

ADVANTAGES

- Excellent compatibility with all paints *
- Indoor use.
- Easy smoothing.
- Seals and cracks.
- Withstands temperatures from -20 ° C to + 80 ° C.
- Excellent adhesion without primer on concrete, aluminum, wood, masonry, PVC.

* Given the great diversity of paintings on the market, it is essential to carry out compatibility tests before any use on site of a product not yet experienced.

PRODUCT USE

Acrylic sealant for various caulking and resumption of cracks before painting.

May be painted.

Not suitable for structural joints

Caulking wood, PVC, aluminum joinery.

Seals between panels, partitions, joinery.

Excellent adhesion on wood, concrete, cement, brick, plaster, aluminum.

TECHNICAL CHARACTERISTICS

- Color : white
- Open time / skin formation : 5 minutes
- Dust free time : 30 minutes
- Drying : 2 mm / 24 h approx.
- Shore hardness A : 15
- Setting temperature implemented : between + 5 ° C and + 40 ° C
- Operating temperature from -20 ° C to + 80 ° C

PREPARATION

SURFACES

In any case, the supports will be clean, dry, healthy, dusted and degreased. On very porous support, it is possible to first apply a dilution constituted of one volume of mastic for two volumes of clean water.

A brushing of the joint lips is recommended before use.

APPLICATION

Eliminate all friable or poorly adhered parts.

Putty is put in place by extrusion, possibly on the bottom of the joint when necessary. After extrusion, tighten and smooth the bead of sealant within 10 minutes with a spatula dipped in soapy water. To avoid that it does not intercalate between the mastic and the surfaces contact, to maintain good adhesion. Let dry a few hours before finishing and proceed to a test.

External grouting / filler must be done in dry weather.

Respect a 24 hours delay (for a temperature of

+ 20 ° C) before exposure of the seal to water (rain or splashing water).

Warning: Cold and / or wet weather may slow down or prevent drying. For an optimal result wait until the sealant has completely dried about 24 hours before paint and check compatibility with the paint applied on a small part.

In general, refer to DTUs and rules in force.

Joint function: refer to DTU 44.1

CLEANING

- Fresh product: with water.
- Dry product: by scratching

CONSOMMATION

About 12 meters of 5 mm diameter cord

STORAGE

18 months in original closed package, stored frost-free between + 5 ° C and + 30 ° C

SECURITY

Bostik LLC

ООО «БОСТИК» 127018 г. Москва, ул. Двинцев, д.12, корп.1

Phone : (495) 787 31 71

Fax :(495) 787 31 72

E-mail : inforu@bostik.com

www.bostik.ru

For more details, consult the safety data sheet on the base www.quick-fds.com or ask us for a copy by fax.

The implementation recommendations are defined in relation to standards of use. They must be respected, but do not dispense with prior testing, especially in the case of first use and / or particular constraints of the support, site or environment. Consult our safety data sheets for precautions for use.

CONDITIONNING

| Code | Packaging | Quantity per pallet | Barcode |
|----------|-----------|---------------------|-------------------|
| 30602639 | Cartouche | 12 | 3549212466 763 |

BOSTIK HOTLINE

Smart help +7 495 787 31 71

