

Declaration of Performance

No.: 40-620-363-01

1. **Unique identification code of the product-type:**
F-type sealant for facade elements INT-EXT S1-type
sealant for sanitary application

2. **Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):**
BOSTIK BAIN CUISINE BLANC 310ML
BOSTIK BAIN CUISINE TRANSPARENT 310ML
BOSTIK BAIN CUISINE BLANC 60ML
 See packaging: batch number, date of manufacture and manufacturing center.

3. **Use or intended use of the construction product in accordance with the applicable harmonized technical specification, as provided for by the manufacturer:**
Joint sealants for non-structural use between facade elements, for indoor and outdoor use. Joint sealants for non-structural use between sanitary elements.

4. **Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):**
Société BOSTIK, le Jade Building — 253 Av du président Wilson — F-9321 La Plaine Saint-Denis Cedex
www.bostik.fr

5. **Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):**
Not applicable

6. **System or systems of Assessment and Verification of Constancy of Performance of the construction product in accordance with Annex V:**
Level 3

7. **In the case of a declaration of performance for a construction product covered by a harmonized standard:**
The notified SKZ — TeConA GmbH laboratory No. NB01213 determined the product-type on the basis of type tests according to system 3 and issued the test reports 106139/13-1 and 106139/13-III.

8. **In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:**
Not applicable

9. **Declared performance:**
Sealants for facade elements

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	Class E	EN 15651-1

Declaration of Performance

Release of hazardous substances	See SDS	2012
Water and air tightness		
Volume loss	≤ 30%	
Resistance to casting	≤ 2 mm	
Adhesion/cohesion, deformation properties under maintained traction after immersion in water	NF	
Adhesion/cohesion, deformation properties under maintained traction (23°C)	NF	
Sustainability	Compliant	

NF= no failure according to EN ISO 11600

Sealants for sanitary applications

Essential characteristics	Performance	Harmonized technical specifications
Water and air tightness		EN 15651-3: 2012
Volume loss	≤ 30%	
Resistance to casting	≤ 2 mm	
Adhesion/cohesion, deformation properties under traction after immersion in water (23°C)	≤ 25%	
Action of microorganisms: growth intensity	1	
Sustainability	Compliant	

NF= no failure according to EN ISO 11600

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified at level 4

Signed for and on behalf of the manufacturer by:

Name and position of company representative

Date /signature/

/stamp/