

Declaration of Performance

No.: 40-600-304-
01

1. Unique identification code of the product-type:

F-type sealant for facade elements INT-EXT class 25HM

2. Type, batch, or serial number or any other element allowing the construction product to be identified in accordance with Article 11 (4):

30114310 XTREM PLUS

See on packaging: batch number, date of manufacture and manufacturing center.

3. Use or intended use of the construction product in accordance with the applicable harmonized technical specification, as specified by the manufacturer:

Joint sealants for non-structural use between facade elements, for indoor and outdoor use including use in cold climate zones.

4. Name, company name or registered trade mark and contact address of the manufacturer in accordance with Article 11 (5):

Société Bostik, Le Jade Building — 253 Av du président Wilson — F-93211 La Plaine Saint-Denis Cedex
www.bostik.fr

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks referred to in Article 12 (2):

Not applicable

6. System or systems of Assessment and. Verification of Constancy of Performance of the construction product in accordance with Annex V:

Level 3

7. In the case of a declaration of performance for a construction product covered by a harmonized standard:

The notified CEBTB laboratory No. 0074 determined the product-type on the basis of type tests according to system 3 and issued the test report

8. In the case of a declaration of performance for a construction product for which a European technical assessment has been issued:

Not applicable

F-type sealant for facade elements INT-EXT class 25HM CC

Declaration of Performance

9. Declared performance:

Sealants for facade elements

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	Class E	EN 15651-1: 2012
Release of hazardous substances	See SDS	
Water and air tightness		
Volume loss	≤ 10%	
Resistance to casting	≤ 3 mm	
Adhesion/cohesion, deformation properties under traction after immersion in (60°C)	NPD	
Adhesion/cohesion, deformation properties under maintained traction after immersion in water (23°C)	NF	
Adhesion/cohesion, deformation properties under traction at -30°C	NPD	
Adhesion/cohesion, deformation properties under maintained traction -30°C	NF	
Sustainability	Compliant	

NF= no failure according to EN ISO 11600

10. The performance of the product identified in points 1 and 2 shall comply with the declared performance indicated in point 9.

This declaration of performance shall be drawn up under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by

Name and position of company representative
Place and Date



Christian KLOPFENSTEIN

F-type sealant for facade elements INT-EXT class 25HM CC