#### Bostik Silmax

Last changed: 28/04/2015

Replaces date: 28/04/2014

Internal No: P0461

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name Bostik Silmax

#### Other information

This safety data sheet applies to all articles.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**RECOMMENDED USES:** Moisture curing sealant based on silane modified polymer. (SMP)

#### 1.3. Details of the supplier of the safety data sheet

#### NATIONAL MANUFACTURER/IMPORTER

Enterprise	Bostik AB
Address	Strandbadsvägen 22
Postal code	251 09 Helsingborg
Country	Sweden
Email	Info.se@bostik.com
Internet	www.bostik.se
Tel	+46 42 19 50 00

# CONTACT PERSONNameEmailTelCountryBostik AB Miljöavdelningen+46 42 19 50 00

1.4. Emergency telephone number		
Emergency Phone	Type of assistance	Opening Hours
+46 8 331231	Swedish Poisons Informations Centre	

#### SECTION 2: Hazards identification

2.1. Classificatior	.1. Classification of the substance or mixture		
DPD			
Classification:	Classification according to Directive 1999/45 / EC DPD. The product is not classified as dangerous according to Directive 1999/45 / EC and its amendments		
CLP Classification:	Classification according to Regulation (EC) No 1272/2008 CLP / GHS: not classified		
Most serious harmful effects::	Further information on potential health effects and symptoms of Section 11		

#### 2.2. Label elements

Signal word: None

#### SUPPLEMENTAL HAZARD INFORMATION (EU)

EUH208 Contains 3-AMINOPROPYLTRIETHOXYSILANE ; N-(3-(TRIMETHOXYSILYL) PROPYL)- ETHYLENE DIAMINE.May produce an allergic reaction. EUH210 Safety data sheet available on request.

#### 2.3. Other hazards

During hardening a small amount methanol.

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Bostik Silmax

Last changed: 28/04/2015

Replaces date: 28/04/2014

Internal No: P0461

Ingredient name	Reg. no.	EC No.	CAS No.	Conc. (wt%)	DPD- Classification	CLP- classification
3-(2-aminoethylamino)propyl trimetoxi silan	01-2119970215- 39	2171646		< 1 %	Xi,R41 - R43	Eye Dam. 1 H318 Skin Sens. 1 H317
dodecanoic bis-(2,2,6,6- tetrametyl-4-piperidinyl)ester	01-2119537297- 32		52829- 07-9	< 1 %	Xi,N,R36 - R51/53	Eye Irrit. 2 H319 Aquatic Chronic 2 H411
3-aminopropyltriethoxysilane	01-2119480479- 24	213-048-4	919-30-2	< 1 %	C,R22 - R34	Acute Tox. 4 H302 Skin Corr. 1B H314

Full text of R-, H- and EUH-phrases: see section 16.

The EUH hazard statements mentioned in CLP-classification are only label elements.

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### INHALATION

Fresh air and rest.

#### INGESTION

Drink a few glasses of water. Contact physician.

#### SKIN

Wash skin thoroughly with soap and water.

#### EYES

Promptly wash eyes with plenty of water while lifting the eye lids.

#### BURNS

Not applicable.

#### GENERAL

When obtaining medical advice, show the safety data sheet or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

Show this Material Safety Datasheet to the doctor.

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING MEDIA:

Extinguish with powder, carbon dioxide, foam or fine water mist.

#### UNSUITABLE EXTINGUISHING MEDIA

Do not use a direct water jet that could spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Carbon dioxide is formed when heated or in a fire.

#### Bostik Silmax

Last changed: 28/04/2015

Replaces date: 28/04/2014

Internal No: P0461

#### 5.3. Advice for firefighters

Wear a self contained breathing apparatus.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### PERSONAL PRECAUTIONS

Wear necessary protective equipment.

#### FOR NON-EMERGENCY PERSONNEL

NB! Risk of slipping due to spillage. Avoid direct contact.

#### 6.2. Environmental precautions

Prevent discharges into the sewage system, watercourses or ground.

#### 6.3. Methods and material for containment and cleaning up

#### METHODS AND MATERIAL

Bank and absorb with inert material (e.g. sand) and treat in accordance with local regulations.

#### 6.4. Reference to other sections

See section 13 for waste disposal.

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Use personal protective equipment. See Section 8 for personal protective equipment.Good working hygiene must always be observed when handling product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep out of the reach of children. Keep in a dry, cool and well-ventilated place. Keep containers tightly closed in closed original packaging or other closed metal or plastic vessel.

#### 7.3. Specific end use(s)

See Technical Data Sheet.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### OTHER INFORMATION REGARDING LIMIT VALUES AND MONITORING

During hardening a small amount methanol.Long-term exposure limit, 8h:200 ppm, 266 mg/m3. Short-term exposure limit 15 min. 250 ppm, 333 mg/m3.

#### 8.2. Exposure controls

#### EXPOSURE SCENARIOS

Good general ventilation should be sufficient to control worker exposure to airborne.

#### APPROPRIATE ENGINEERING CONTROLS

The work place and work methods shall be oganized in such a way that direct contact with the product is prevented.

#### **Bostik Silmax**

Last changed: 28/04/2015

Replaces date: 28/04/2014

Internal No: P0461

#### EYE PROTECTION

Eye protection is recommended when there is a risk of direct contact or splashes

#### SKIN PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

#### HAND PROTECTION

Protective gloves shall be used when there is a risk of direct contact or splashes. Wear appropriate clothing to prevent any possibility of skin contact. Protective gloves (polyethylene, PVC).

#### **RESPIRATORY PROTECTION**

If ventilation is insufficient, use a breathing mask with filter for organic vapours (type A).

#### OTHER INFORMATION

When using do not eat, drink or smoke. Wash your hands thoroughly after handling and before eating or smoking.

#### LIMITATION OF ENVIRONMENTAL EXPOSURE

Prevent discharge into the sewage system or the immediate environment.

#### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

STATE Paste.

**COLOUR** Not translated to English

#### SOLUBILITY Uncured product in white spirit.

Parameter	Value/unit	Method/reference	Observation
pH (concentrate)	No data		
pH (solution for use)	No data		
Melting point	No data		
Freezing point	No data		
Initial boiling point and boiling range	No data		
Flash point	> 150 °C		
Evaporation rate	No data		
Flammability (solid, gas)	No data		
Flammability limits	No data		
Explosion limits	No data		
Vapour pressure	No data		
Vapour density	No data		
Relative density	No data		
Partition coefficient	No data		
Auto-ignition temperature	No data		
Decomposition temperature	No data		
Viscosity	No data		

#### 9.2. Other information

Parameter	Value/unit	Method/reference	Observation
Density	1,5 -		
	·	·	·

Note no.

Comments

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known.

#### **Bostik Silmax**

Last changed: 28/04/2015

Replaces date: 28/04/2014

Internal No: P0461

#### 10.2. Chemical stability

Stable under recommended storage and handling conditions.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

#### 10.5. Incompatible materials

Strong alkalis. Strong acids. Oxidising agent.

#### 10.6. Hazardous decomposition products

Carbon dioxide is formed when heated or in a fire.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Acute toxicity - oral

Ingestion of large quantities may cause stomach ache, nausea and diarrhoea.

#### Acute toxicity - dermal

Prolonged exposure may cause irritation.

#### Acute toxicity - inhalation

The during curing released substances may irritate respiratory tracts if work takes place in confined badly ventilated rooms.

#### Serious eye damage/eye irritation

May cause irritation.

#### Carcinogenic properties

No known significant effects or critical hazards.

#### **Reproductive toxicity**

No known significant effects or critical hazards.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

## ACUTE AQUATIC TEST RESULTS

No information available

#### ECOTOXICITY

No information available

#### 12.2. Persistence and degradability

No information available

**Bostik Silmax** 

Last changed: 28/04/2015

Replaces date: 28/04/2014

Internal No: P0461

#### 12.3. Bioaccumulative potential

No information available

#### 12.4. Mobility in soil

No information available

#### 12.5. Results of PBT and vPvB assessment

Not applicable.

#### 12.6. Other adverse effects

The product is not classified as dangerous to the environment according to Scandinavian or ECC criteria and information available and known to us.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### GENERAL REGULATIONS

Dried product in limited volumes may be treated as normal industrial waste. When handling larger volumes consult local authorities and local waste disposal organisation.

#### CATEGORY OF WASTE

EWC-Code 080410

#### SECTION 14: Transport information

Classified as Dangerous Goods: No

Land transport	t (ADR/RID)			
14.1. UN number	Not applicable	14.4. Packing group	Not applicable	
14.2. UN proper shipping name	Not applicable	14.5. Environmental hazards	Not applicable	
14.3. Transport hazard class(es)	Not applicable			
Hazard label(s)	Not applicable			
Hazard identification number	Not applicable	Tunnel restriction code	Not applicable	

Inland water wa	ys transport (ADN)		
14.1. UN number	Not applicable	14.4. Packing Not applicable group	
14.2. UN proper shipping name	Not applicable	14.5. Not applicable Environmental hazards	
14.3. Transport hazard class(es)	Not applicable		
Hazard Iabel(s)	Not applicable		
Environmental hazard in tank vessels	Not applicable		

#### **Bostik Silmax**

Last changed: 28/04/2015

Replaces date: 28/04/2014

Internal No: P0461

Sea transport	(IMDG)			
14.1. UN number	Not applicable	14.4. Packing group	Not applicable	
14.2. UN proper shipping	Not applicable	14.5. Environmental hazards	Not applicable	
name 14.3. Transport hazard class(es)	Not applicable			
Hazard label(s)	Not applicable			
Sub Risk: IMDG Code segregation group	Not applicable Not applicable			
Marine pollutant	Not applicable			
Substance name(s) on marine pollutant	Not applicable			
EMS:	Not applicable			

Air transport	: (ICAO-TI / IATA-DGR)		
14.1. UN number	Not applicable	14.4. Packing Not applicable group	
14.2. UN proper shipping name	Not applicable		
14.3. Transport hazard class(es)	Not applicable		
Hazard label(s)	Not applicable		

#### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### OTHER REGULATORY INFORMATION

Safety data sheet available for professional use on request.

#### PROVISIONS

Safety, health and environmental regulations / legislation specific for the substance or mixture. EU Regulation (EC) No 1907/2006 (REACH).

### 15.2. Chemical safety assessment

#### OTHER INFORMATION

Chemical safety assessment has not been performed.

#### **SECTION 16: Other information**

**ISSUED:** 28/04/2015

#### VENDOR NOTES

The product is not classified as dangerous to the environment according to Scandinavian or ECC criteria and information available and known to us.

#### Bostik Silmax

Last changed: 28/04/2015

Replaces date: 28/04/2014

Internal No: P0461

LI ST OF	RELEVANT R-PHRASES	
R22	Harmful if swallowed.	

R34	Causes burns.
11.0 +	oddses barris.

- R36 Irritating to eyes.
- R41 Risk of serious damage to eyes.
- R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### LIST OF RELEVANT H-STATEMENTS

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

#### USER NOTES

Version 2.

#### OTHER INFORMATION

The information on this Safety Data Sheet is based on our present knowledge and applicable EU and national laws. The product should not be used for other purposes than as specified in paragraph 1, without a prior written instruction from the supplier. It is always the full responsibility of the user to follow the requirements according to the law. The information on the Safety Data Sheet is intended to describe the security requirements of the product and is not a guarantee for the product quality.