

**BOSTIK SOL CONTACT NM**  
Supersedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product Identifier

**Product Name** BOSTIK SOL CONTACT NM  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Adhesives.  
**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik SA  
Immeuble "Le Jade"  
253 Avenue du President Wilson  
93211 La Plaine Saint Denis  
France  
Tel: +33 (0)1 55 99 90 00  
Fax: +33 (0)1 55 99 90 01

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**Emergency Telephone** No information available

## Section 2: HAZARD IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

<b>Skin Corrosion/Irritation</b>	Category 2 - (H315)
<b>Serious eye damage/eye irritation</b>	Category 2 - (H319)
<b>Specific target organ toxicity (single exposure)</b>	Category 3 - (H336)
<b>Chronic aquatic toxicity</b>	Category 2 - (H411)
<b>Flammable Liquids</b>	Category 2 - (H225)

### 2.2. Label Elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains : Methyl ethyl ketone, Methylcyclohexane, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane

# Safety Data Sheet

BOSTIK SOL CONTACT NM  
Supersedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01



**Signal Word**  
DANGER

## Hazard statements

H225 - Highly flammable liquid and vapour  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

## Special provisions concerning the labelling of certain mixtures

EUH208 - Contains rosin & methylols. May produce an allergic reaction

## Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children  
P280 - Wear protective gloves and eye/face protection  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P337 + P313 - If eye irritation persists: Get medical advice/attention  
P271 - Use only outdoors or in a well-ventilated area  
P261 - Avoid breathing vapours  
P312 - Call a POISON CENTER or doctor if you feel unwell  
P101 - If medical advice is needed, have product container or label at hand  
P403 - Store in a well-ventilated place  
P273 - Avoid release to the environment  
P501 - Dispose of contents/ container to an approved waste disposal plant

## Additional information

This product requires tactile warnings if supplied to the general public

## 2.3. Other Hazards

### General Hazards

In use may form flammable/explosive vapour-air mixture.

### PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Mixture

### 3.2 Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Methyl ethyl ketone	201-159-0	78-93-3	>25 - <40	Eye Irrit. 2 (H319) STOT SE 3 (H336)		01-2119457290-43 -XXXX

# Safety Data Sheet

**BOSTIK SOL CONTACT NM**  
**Supersedes Date:** 24-Apr-2017

**Revision Date** 09-Jun-2017  
**Version** 2.01

				Flam. Liq. 2 (H225) (EUH066)		
Methylcyclohexane	203-624-3	108-87-2	>25 - <40	Skin Irrit. 2 (H315) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)		01-2119556887-18 -XXXX
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane	921-024-6	--	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225)		01-2119475514-35 -XXXX
Rosin	232-475-7	8050-09-7	0.1- <1	Skin Sens. 1 (H317)		01-2119480418-32 -XXXX
Xylenes (o-, m-, p- isomers)	215-535-7	1330-20-7	0.1- <1	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226)	::	01-2119488216-32 -XXXX
Hexane	203-777-6	110-54-3	0.1- <1	Skin Irrit. 2 (H315) Repr. 2 (H361f) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	STOT RE 2 :: C>=5%	01-2119480412-44 -XXXX
Zinc oxide	215-222-5	1314-13-2	0.1- <1	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119463881-32 -XXXX
Methylols	-	UNKNOWN	0.1- <1	Skin Sens. 1 (H317)		No Data Available

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL.

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Section 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### General Advice

Immediate medical attention is required. In case of accident or being unwell, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a doctor.

#### Inhalation

Remove to fresh air. If symptoms persist, call a doctor. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapours.

#### Skin Contact

Wash off immediately with plenty of water. Wash contaminated clothing before reuse. If skin irritation persists, call a doctor. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

# Safety Data Sheet

**BOSTIK SOL CONTACT NM**  
Supercedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

---

<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a doctor. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
<b>Ingestion</b>	Immediate medical attention is not required. Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a doctor.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** Treat symptomatically.

### **Section 5: FIRE-FIGHTING MEASURES**

#### 5.1. Extinguishing media

**Suitable Extinguishing Media**

Use CO<sub>2</sub>, dry chemical, or foam. Move containers from fire area if you can do it without risk.

**Unsuitable Extinguishing Media**

Use water spray or fog; do not use straight streams

#### 5.2. Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). EXTREMELY FLAMMABLE.

#### 5.3. Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

### **Section 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal Precautions**

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

Water spray may reduce vapour; but may not prevent ignition in closed spaces.

**For emergency responders**

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

#### 6.3. Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labelled containers. Dam up. Soak up with inert

# Safety Data Sheet

**BOSTIK SOL CONTACT NM**  
Supersedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

## 6.4. Reference to other sections

Reference to other sections See Section 12: ECOLOGICAL INFORMATION  
Section 7: HANDLING AND STORAGE  
Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Section 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

#### **Advice on safe handling**

Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapours/spray.

#### **General Hygiene Considerations**

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

### 7.2. Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep tightly closed in a dry and cool place. Keep in properly labelled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

### 7.3. Specific end use(s)

#### **Other Information**

Recommendation(s). Observe technical data sheet.

## **Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1. Control parameters

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical Name	European Union
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m <sup>3</sup> STEL: 300 ppm STEL: 900 mg/m <sup>3</sup>
Xylenes (o-, m-, p- isomers) 1330-20-7	TWA: 50 ppm TWA: 221 mg/m <sup>3</sup> STEL: 100 ppm STEL: 442 mg/m <sup>3</sup> S*
Hexane 110-54-3	TWA: 20 ppm TWA: 72 mg/m <sup>3</sup>

**Derived No Effect Level (DNEL)** No information available

**Predicted No Effect Concentration (PNEC)** No information available.

### 8.2. Exposure controls

**Engineering Controls** Ensure adequate ventilation, especially in confined areas.

# Safety Data Sheet

BOSTIK SOL CONTACT NM  
Supersedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

## Personal Protective Equipment

<b>Eye/Face Protection</b>	Tight sealing safety goggles. Face protection shield.
<b>Hand Protection</b>	Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
<b>Skin and Body Protection</b>	Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.
<b>Respiratory Protection</b>	In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. In case of inadequate ventilation wear respiratory protection.
<b>Recommended Filter type:</b>	Organic gases and vapours filter conforming to EN 14387.

**Environmental Exposure Controls** Do not allow into any sewer, on the ground or into any body of water.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<b>Physical State</b>	Liquid	
<b>Appearance</b>	Viscous	
<b>Colour</b>	Yellow	
<b>Odour</b>	Solvent	
<b>Odour Threshold</b>	No information available	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>pH</b>	No information available	
<b>Melting point/freezing point</b>	No information available	
<b>Boiling Point</b>	56 °C / 132.8 °F	
<b>Flash Point</b>	-18 °C / -0.4 °F	CC (closed cup)
<b>Evaporation Rate</b>	No information available	
<b>Flammability (solid, gas)</b>	No information available	Not applicable for liquids
<b>Flammability Limit in Air</b>		
Upper Flammability Limit	13	
Lower Flammability Limit	1	
<b>Vapour Pressure</b>	< 110	kPa @ 23 °C
<b>Vapour Density</b>	No information available	
<b>Relative Density</b>	No information available	
<b>Water Solubility</b>	No information available	
<b>Solubility in Other Solvents</b>	No information available	
<b>Partition Coefficient</b>	No information available	
<b>Autoignition Temperature</b>	No information available	
<b>Decomposition Temperature</b>	No information available	
<b>Explosive Properties</b>	No information available	
<b>Explosive Limits</b>	No information available	
Upper	No information available	
Lower	No information available	
<b>Oxidising Properties</b>	No information available	
<b>Kinematic Viscosity</b>	> 200 mm <sup>2</sup> /s	@ 40°C
<b>Dynamic Viscosity</b>	1400 - 2500 mPa s	@ 23 °C

### 9.2. Other information

<b>Softening Point</b>	No information available
<b>Molecular Weight</b>	No information available
<b>Solvent content (%)</b>	No information available
<b>Solid content (%)</b>	24.5
<b>Density</b>	0.825 g/cm <sup>3</sup>
<b>Bulk Density</b>	No Data Available
<b>VOC content (%)</b>	

## Section 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

# Safety Data Sheet

**BOSTIK SOL CONTACT NM**  
Supercedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

Stable under recommended storage conditions.

## **10.2. Chemical stability**

Stable under recommended storage conditions.

### Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

## **10.3. Possibility of hazardous reactions**

### **Possibility of Hazardous Reactions**

None under normal processing.

## **10.4. Conditions to avoid**

Heat, flames and sparks.

## **10.5. Incompatible materials**

Strong acids and bases.

## **10.6. Hazardous decomposition products**

None under normal use conditions.

## **Section 11: TOXICOLOGY INFORMATION**

### **11.1. Information on toxicological effects**

#### **Product Information**

No information or data specific to the product on this toxicological (health) effect is available.

<b>Inhalation</b>	No Data Available.
<b>Eye contact</b>	No Data Available.
<b>Skin Contact</b>	No Data Available.
<b>Ingestion</b>	No Data Available.
<b>Sensitisation</b>	No Data Available.

**Skin Corrosion/Irritation** Not applicable.

**Serious eye damage/eye irritation** Not applicable.

**Sensitisation** Not applicable.

**Germ Cell Mutagenicity** Not applicable.

**Carcinogenicity** Not applicable.

**Reproductive Toxicity** No information available.

**STOT - Single Exposure** No information available.

**STOT - Repeated Exposure** No information available.

**Target Organ Effects** Central nervous system, Eyes, Respiratory system, Skin.

**Aspiration Hazard** No information available.

# Safety Data Sheet

BOSTIK SOL CONTACT NM  
Supersedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

## Numerical measures of toxicity

### Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 3,841.00 mg/kg  
ATEmix (dermal) 4,815.00 mg/kg

## Component Information

**Toxicity Data** Data obtained on the component(s) include

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone 78-93-3	= 2483 mg/kg ( Rat )	= 5000 mg/kg ( Rabbit )	= 11700 ppm ( Rat ) 4 h
Methylcyclohexane 108-87-2	> 3200 mg/kg ( Rat )	>2920 mg/Kg bw (rat) 24 hour	>23 mg/l (vapour) (Rat- OECD 403)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane --	LD50 >5840 mg/kg (Rat)	LD50 >2800-3100 mg/kg (Rat)	-
Rosin 8050-09-7	>2800 mg/Kg (rat)	> 2500 mg/kg ( Rabbit )	= 1.5 mg/L ( Rat ) 4 h
Hexane 110-54-3	= 25 g/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 48000 ppm ( Rat ) 4 h
Zinc oxide 1314-13-2	> 5000 mg/kg ( Rat )	-	LC50 (4h) >5.7 mg/l

## **Section 12: ECOLOGICAL INFORMATION**

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life with long lasting effects

### Component Information

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea	M-Factor
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50 96 h 3130 - 3320 mg/L (Pimephales promelas flow-through)	EC50 48 h > 308 mg/L (Daphnia magna )	
Methylcyclohexane 108-87-2	10 mg/l (Pseudokirchneriella subcapitata - OECD 201)	2.07 mg/l (Oryzias latipes )	3 mg/l (Daphnia magna - OECD 202)	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane --	EL50 (72h)= 26 mg/L (Pseudokirchneriella subcapitata) OECD 201	LL50 (96h) =12 mg/L Fish (Oncorhynchus mykiss) OECD 203	EL50 (48h) =3mg/L (Daphnia magna) OECD 202	
Rosin 8050-09-7	EC50 72 h = 400 mg/L (Desmodesmus subspicatus)	LC50 (96h) >10mg/L Fish (Danio rerio)	EC50 48 h >100 mg/L (Daphnia magna )	
Xylenes (o-, m-, p- isomers) 1330-20-7	-	LC50 96 h 13.5 - 17.3 mg/L (Oncorhynchus mykiss )	EC50 48 h = 3.4 mg/L (water flea)	
Hexane 110-54-3	-	LC50 96 h 2.1 - 2.98 mg/L (Pimephales promelas flow-through)	EC50 24 h > 1000 mg/L (Daphnia magna )	
Zinc oxide 1314-13-2	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L Fish (Danio rerio)	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)	1

### 12.2. Persistence and degradability

No information available.



# Safety Data Sheet

BOSTIK SOL CONTACT NM  
Supercedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

## 12.3. Bioaccumulative potential

No information available.

**Partition coefficient** No information available

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

## 12.6. Other Adverse Effects

No information available

## **Endocrine Disruptor Information**

## **Section 13: DISPOSAL CONSIDERATIONS**

### 13.1. Waste treatment methods

<b>Waste from Residues/Unused Products</b>	Disposal should be in accordance with applicable regional, national and local laws and regulations.
<b>Contaminated Packaging</b>	Improper disposal or reuse of this container may be dangerous and illegal.
<b>European Waste Catalogue</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
<b>Other Information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## **Section 14: TRANSPORTATION INFORMATION**

### ADR

<b>14.1 UN/ID no</b>	UN1133
<b>14.2 Proper Shipping Name</b>	Adhesives, Environmentally Hazardous
<b>14.3 Hazard Class</b>	3
<b>Hazard Labels</b>	3
<b>14.4 Packing Group</b>	III
<b>Description</b>	UN1133, Adhesives, 3, III, (D/E), Environmentally Hazardous
<b>14.5 Environmental Hazard</b>	yes
<b>14.6 Special Provisions</b>	640E
<b>Classification Code</b>	F1
<b>Tunnel restriction code</b>	(D/E)
<b>Limited Quantity (LQ)</b>	5 L
<b>ADR Hazard Id (Kemmler Number)</b>	30

### IMDG

<b>14.1 UN/ID no</b>	UN1133
<b>14.2 Proper Shipping Name</b>	Adhesives (Methylcyclohexane), Marine Pollutant
<b>14.3 Hazard Class</b>	3
<b>14.4 Packing Group</b>	III
<b>Description</b>	UN1133, Adhesives (Methylcyclohexane), 3, III, (-18°C c.c.), Marine Pollutant

# Safety Data Sheet

BOSTIK SOL CONTACT NM  
Supersedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

- 14.5 Marine Pollutant** PP  
This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO
- 14.6 Special Provisions** 223, 955  
**Limited Quantity (LQ)** 5 L  
**EmS-No** F-E, S-D
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** No information available

## RID

- 14.1 UN/ID no** UN1133  
**14.2 Proper Shipping Name** Adhesives, Environmentally Hazardous  
**14.3 Hazard Class** 3  
**Hazard Labels** 3  
**14.4 Packing Group** III  
**Description** UN1133, Adhesives, 3, III, Environmentally Hazardous  
**14.5 Environmental Hazard** yes  
**Classification Code** F1  
**14.6 Special Provisions** 640E  
**Limited Quantity (LQ)** 5 L

## ICAO (air)

- 14.1 UN/ID no** UN1133  
**14.2 Proper Shipping Name** Adhesives  
**14.3 Hazard Class** 3  
**14.4 Packing Group** III  
**Description** UN1133, Adhesives, 3, III  
**14.5 Environmental Hazard** yes  
**14.6 Special Provisions** A3

## IATA

- 14.1 UN/ID no** UN1133  
**14.2 Proper Shipping Name** Adhesives  
**14.3 Hazard Class** 3  
**14.4 Packing Group** III  
**Description** UN1133, Adhesives, 3, III  
**14.5 Environmental Hazard** yes  
**14.6 Special Provisions** A3  
**Limited Quantity (LQ)** 10 L  
**ERG Code** 3L

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# Safety Data Sheet

**BOSTIK SOL CONTACT NM**  
Supersedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

or

P5b - FLAMMABLE LIQUIDS

or

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## National Regulations

### France

#### Occupational Illnesses (R-463-3, France)

Chemical Name	French RG number
Methyl ethyl ketone 78-93-3	RG 84
Methylcyclohexane 108-87-2	RG 84
Rosin 8050-09-7	RG 65, RG 66
Xylenes (o-, m-, p- isomers) 1330-20-7	RG 4bis, RG 84
Hexane 110-54-3	RG 59, RG 84

### Germany

#### Ordinance on Industrial Safety and Health - Germany - BetrSichV

Flammable liquid (R11), EEC: refer to Annex III No. 1 (fire and explosion hazards) and § 7 paragraph 4

### Netherlands

#### List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical Name	Netherlands
Xylenes (o-, m-, p- isomers) 1330-20-7	Development (Category 2)
Hexane 110-54-3	Fertility (Category 2)

# Safety Data Sheet

**BOSTIK SOL CONTACT NM**  
Supercedes Date: 24-Apr-2017

Revision Date 09-Jun-2017  
Version 2.01

## 15.2. Chemical safety assessment

No information available

## **Section 16: OTHER INFORMATION**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H304 - May be fatal if swallowed and enters airways  
H411 - Toxic to aquatic life with long lasting effects  
H225 - Highly flammable liquid and vapour  
H361f - Suspected of damaging fertility  
H373 - May cause damage to organs through prolonged or repeated exposure if inhaled  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H319 - Causes serious eye irritation  
H317 - May cause an allergic skin reaction  
EUH066 - Repeated exposure may cause skin dryness or cracking

#### **Legend**

SVHC: Substances of Very High Concern for Authorisation:

#### **Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals  
STOT (RE): Specific target organ toxicity - Repeated exposure  
STOT (SE): Specific target organ toxicity - Single exposure  
EWC: European Waste Catalogue

#### **Key literature references and sources for data**

Classification and labeling data calculated from data received from raw material suppliers

**Prepared By** Product Safety & Regulatory Affairs

**Revision Date** 09-Jun-2017

#### Indication of changes

**Revision Note** SDS sections updated: 9, 11.

**Training Advice** Provide adequate information, instruction, and training for operator

**Additional information** No information available

**This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006**

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**